





1. MATERIAL:

HOUSING: THERMOPLASTIC SEAL: SILICONE RUBBER


2. MODIFICATIONS: N/A

- 3. SPECIFICATIONS:
  - 3.1 CURRENT RATING: 13 AMPS
  - 3.2 OPERATING TEMPERATURE: -55°C TO +125°C
  - 3.3 DIELECTRIC WITHSTANDING VOLTAGE: LESS THAN 2 MILLIAMPS CURRENT LEAKAGE @ 1500 VOLTS AC.
  - 3.4 INSULATION RESISTANCE: 1000 MEGOHMS MIN @ 25°C.
  - 3.5 MOISTURE RESISTANCE:


IP68(1M OF WATER FOR A PERIOD OF 24 HOURS, MATED CONDITION)

IP69K(MATED CONDITION)

- 3.6 MATING CYCLE DURABILITY: 100 CYCLES
- 3.7 RoHS COMPLIANT
- 4. MATING PART: AT04-4P\* RECEPTACLE (\* = MODIFICATIONS AND COLORS)
- 5. ALL DIMENSIONS ARE FOR REFERENCE USE ONLY.





CONTACT	MIN. INSUL	MAX. INSUL	TYPICAL
SIZE	O.D.	O.D.	WIRE RANGE
40	2.24 mm	3.68 mm	14 - 20 AWG
16	(.088 in)	(.145 in)	(2.0-0.5mm²)



PART NUMBER CHART		
COLOR PART NUMBER		
GREY	AT06-4S	
BLACK	AT06-4S-BLK	
BLUE	AT06-4S-BLU	
BROWN	AT06-4S-BRN	
GREEN	AT06-4S-GRN	
RED	AT06-4S-RED	
WHITE	AT06-4S-WHT	
YELLOW	AT06-4S-YEL	
ORANGE AT06-4S-ORG		

		REVISIONS			
REV	ECO	DESCRIPTION	DATE	BY	APPR
A3	-	RELEASE NEW DWG FORMAT	26DEC13	DRP	
A4	C0540S	UPDATE DIMENSIONS	22JUN16	JONY	TOMMY
A5	-	ADD COLOR OPTION	23NOV20	LOUIE	TOMMY





STANDARD MOLDED COLOR IS GREY. ADDITIONAL COLORS SHOWN IN PART NUMBER CHART ARE AVAILABLE VIA SPECIAL ORDER.

	SEE PART N	RT NUMBER CHART			REF: DT064S, DT064S-E004, DT064S-P012		
	PART NUMBER				DESCRIPTION	ITEM	
QUANTITY		- 1	MAT	ERI	ALS LIST		
	WISE SPECIFIED	SIGN	IATURES	DATE	Amphonol		
All dimensions a Tolerances are a PL DEC ±0.30		DRAWN:	LOUIE	23NOV20	Amphenol		
2 PL DEC ±0.15 3 PL DEC ±0.08	Angles ±1°	CHECKED:	ORION	25NOV20	44724 Morley Drive Clinton Township, MI 48036		
3) Note reference	<b>-</b> 🗴	ENGINEER:					
MATERIAL SPECIFICA	TIONS:	APPROVAL:	TOMMY	27NOV20			
	CL				PLUG. 4 SOCKET. AT SERIES		
INFORMAT			G IS SUPPLIED I		T 200, T 000K21, AT 02K120		
PROCESS SPECIFICA	TIONS:	SPECIFICATION SHOWN HERE THE AMPHENIOF REPRODU	ONS AND PERFO ON ARE THE PR OL CORPORATION CTION ARE IMPL ARE SUBJECT T	RMANCE DATA ROPERTY OF DN. NO RIGHTS LIED. ALL	- ATOM 40 VAVA	15 15	
NEXT ASS'Y:			RING VARIATION		SCALE: NONE SHEET 1 OF 1		

DWG NO:

PLUG, 4 SOCKET, AT SERIES

AT06-4S-XXX

REV: **A5** SH: 1

## A Series™ - Contact Size 16 Options (Works with: AT, ATV, AHD-9, ARC, DuraMate and PanelMate Series)

	Machined Contacts, Sockets & Pins				
Part Number	Description	Size	AWG	Туре	
AT60-215-1631	Male Contact - Pin, Gold-plated	16	14	Machined	
AT62-209-1631	Female Contact - Socket, Gold-plated	16	14	Machined	
AT60-215-16141	Male Contact - Pin, Nickel-plated	16	14	Machined	
AT62-209-16141	Female Contact - Socket, Nickel-plated	16	14	Machined	
AT60-202-1631	Male Contact - Pin, Gold-plated	16	16-20	Machined	
AT62-201-1631	Female Contact - Socket, Gold-plated	16	16-20	Machined	
AT60-202-16141	Male Contact - Pin, Nickel-plated	16	16-20	Machined	
AT62-201-16141	Female Contact - Socket, Nickel-plated	16	16-20	Machined	
AT60-202-1631-22	Male Contact - Pin, Gold-plated	16	22-24	Machined	
AT62-201-1631-22	Female Contact - Socket, Gold-plated	16	22-24	Machined	
AT60-202-16141-22	Male Contact - Pin, Nickel-plated	16	22-24	Machined	
AT62-201-16141-22	Female Contact - Socket, Nickel-plated	16	22-24	Machined	

	Tooling - Machined Contacts				
Part Number	Description				
AUTK-20	Hand Crimp Tool, Size 20				
AUTK-100	Universal Heavy Duty Contact Crimping Tool Kit, Size 12/16/20				
CA-5D12	Universal Hand Crimp Tool, Size 12/16/20				
CA-5E12	Pneumatic Crimp Tool, Size 12/16/20				

Contact Removal Tools (For both Machined or Stamped & Formed Contacts)			
Part Number	Description		
ATRT-100	Contact and Wedgelock Extraction Tool		
AT11-310-1605	Contact Removal Tool, Plastic, Size 16		

Sealing Plugs (For both Machined or Stamped & Formed Contacts)				
Part Number	Description			
A114017	Sealing Plug, Size 16, White			
A114017-SR	Sealing Plug, Size 16, SR01 Series, Black			
AT13-217-1605	Locking Sealing Plug, Size 16, Grey			
AT13-217-1605-SR	Locking Sealing Plug, Size 16, SR01 Series, Red			

Stamped & Formed Contacts, Sockets & Pins				
Part Number	Description	Size	AWG	Туре
AT60-14-0144	Male Contact - Pin, Gold-plated	16	14-16	Stamped & Formed
AT62-14-0144	Female Contact - Socket, Gold-plated	16	14-16	Stamped & Formed
AT60-14-0122	Male Contact - Pin, Nickel-plated	16	14-16	Stamped & Formed
AT62-14-0122	Female Contact - Socket, Nickel-plated	16	14-16	Stamped & Formed
AT60-16-0144	Male Contact - Pin, Gold-plated	16	16-18	Stamped & Formed
AT62-16-0144	Female Contact - Socket, Gold-plated	16	16-18	Stamped & Formed
AT60-16-0122	Male Contact - Pin, Nickel-plated	16	16-18	Stamped & Formed
AT62-16-0122	Female Contact - Socket, Nickel-plated	16	16-18	Stamped & Formed
AT60-16-0644	Male Contact - Pin, Gold-plated	16	18-20	Stamped & Formed
AT62-16-0644	Female Contact - Socket, Gold-plated	16	18-20	Stamped & Formed
AT60-16-0622	Male Contact - Pin, Nickel-plated	16	18-20	Stamped & Formed
AT62-16-0622	Female Contact - Socket, Nickel-plated	16	18-20	Stamped & Formed
AT60-16-0844	Male Contact - Pin, Gold-plated	16	20-22	Stamped & Formed
AT62-16-0844	Female Contact - Socket, Gold-plated	16	20-22	Stamped & Formed
AT60-16-0822	Male Contact - Pin, Nickel-plated	16	20-22	Stamped & Formed
AT62-16-0822	Female Contact - Socket, Nickel-plated	16	20-22	Stamped & Formed

	Tooling - Stamped & Formed Contacts		
MFX-3950	Crimp Die - Size 16, 18-20AWG		
MFX-3953	Crimp Die - Size 16, 16-18AWG		
MFX-3975	Crimp Die - Size 16, 14-16AWG		
MFX-3990	Crimp Die - Size 16, 20-22AWG		
ATT-16-00	Hand Crimp Tool - Size 16, 14-16AWG		
ATT-16-01	Hand Crimp Tool - Size 16, 18-20AWG		
ATT-1612-03	Hand Crimp Tool - Size 16, 20-22AWG		