


Date	SYM	REVISION RECORD	AUTH	DR.	CK.
11/07/14	E	UPDATED TO ROHS 2 COMPLIANT	T.B.	B.S.	
07/07/17	F	DIM. 5.0 WAS 3.18 DIM. 150.0 WAS 152.40 DIM. 18.91 WAS 18.71 DIM. 13.50 WAS 13.49 DIM. 11.50 WAS 11.53 DIM. 25.85 WAS 25.91	T.B.	B.S.	
07/17/17	G	REMOVED DIM. Ø2.00	T.B.	B.S.	




NOTES:

1. MATERIAL:

HOUSING : BLACK POLYPROPYLENE
 FLAMMABILITY RATING -UL94 HB, UL FILE NO. E216959
 TEMPERATURE RANGE: -10°C to +100°C
 RIVETS: BRASS, NICKEL PLATED.
 SPRING: SPRING STEEL, NICKEL PLATED.
 CONTACTS: SPRING STEEL, NICKEL PLATED.
 WIRE: 26 AWG, UL1007, CSA, TR64, 300V, 80°C
 CONTACT RESISTANCE: UNDER 50mΩ FOR +/- CONTACTS PER
 EIA-540J000

ROHS 2 COMPLIANT

Tolerance (Except as noted)	 Memory Protection Devices, Inc 200 Broad Hollow Road, Farmingdale, New York 11735	Scale	Drawn By B.S.
			Approved By T.B.
decimal ±.5 (.020)	Title FOUR "AAA" CELL HOLDER WITH WIRE LEADS	Date 07/17/17	
Fractional ± .8 (.030)		Drawing Number BH24AAAW	
Angular ± 3°			