

## SUMMARY

### # Wires

*Image is for illustrative purpose only*

Series	2M	<b>Download</b> <a href="#">Request a quote</a> <a href="#">Catalog</a>
Termination type	No contacts / Accessory	
IP rating	68 mated (mating interface)	
AWG wire size	0.00 - 0.00	
Cable Ø	0.00 - 0.00 mm	
Status	Active	

## TECHNICAL DETAILS

### Mechanics

Shell Style/Model	BMK*: Blanking caps, large washer for fixed sockets(knurled grip)
Keying	No keying
Housing Material	Brass (chrome plated [SAE AMS 2460]) shell and collet nut, nickel plated [SAE AMS QQ N 290] brass latch sleeve and mid pieces
Weight	6.88 g

### Performance

Configuration
Insulator
Rated Current

### Specifications

Contact LEMO for performance details.

### Others

Temp (min / max): -55°C / +135°C
Humidity (max): 21 days at 95%
Gunfire vibration: 25 Hz - 2000 Hz, 3 axis (Apache helicopter)
Vibration-Sine: 30 g, 3 axes, 12 hr [10 Hz - 2000 Hz]

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

Vibration-Random: 37.8 g rms - 3 axes, 4 hr amb [50 Hz - 2000 Hz]  
Shock Resistance: 300 g [ 3 ms]  
Lighting strike EIA 364-75: 10K amps - 6 times  
Thermal shock: 5 cycles: -65°C to +150°C  
EMI Shielding EIA 364-66A: >= 80 dB (1 GHz), >=70 dB (3 GHz), >= 58 dB (6 GHz), >= 40 dB (10 GHz)  
Salt Spray Corrosion: >1000 hr

# DRAWINGS

No keying

## Dimensions

	A	C	L	N	P	X
mm.	17.6	17.2	17.2	21	23.4	85
in.	0,69	0,68	0,68	0,83	0,92	3,35

# RECOMMENDED BY LEMO

## Tools

LEMO products and services are provided “as is”. LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.