## The Cowboy 5G

Ceiling Mount Dome Antenna



## BT151007

## The ideal ceiling mount antenna for transmitting & receiving in 360-degree view

- Built for the USA band ranges covering 617 MHz to 6000 MHz
- Wideband omnidirectional indoor antenna for use with signal boosting systems
- Low return loss and stable performance in a compact, lightweight design
- Up to +5 dBi gain, designed for 50 Ohm Systems
- Easy to install

| (B) and (B) |             |  |
|-------------|-------------|--|
|             | 5G<br>READY |  |
|             | READY       |  |
|             |             |  |
|             |             |  |

2500 MHz

VERTICAL


900 MHz

1710 MHz

2500 MHz

| ELECTRICAL     |            | Product Specifications may change without prior notice. |          |         |           |           |           |                    |
|----------------|------------|---|----------|---------|-----------|-----------|-----------|--------------------|
| ltem No.       |            |   | BT151007 |         |           | PATTERNS  |           |                    |
| Frequency Ra   | nge        | MHz   | 617-698  | 698-960 | 1710-2700 | 3400-4000 | 4900-6000 | HORIZONTAL         |
| Gain           |            | dBi   | 1.8±0.5  | 2.0±0.5 | 3.0±1.0   | 4.0±1.0   | 4.5±1.0   |                    |
| VSWR           |            |   | ≤1.8     | ≤1.8    | ≤1.5      | ≤1.7      | ≤1.7      | 10                 |
| Polarization   |            | Vertical 900 MHz  |          |         |           |           |           | 900 MHz            |
| Beam Width     |            | deg   |          |         | 360       |           |           |                    |
| Bearr Width    | Vertical   |   | 90       | 80      | 35        | 30        | 28        | n <u>n n n n</u> n |
| PIM, 3rd Order | , 2 x 20 W | dBc   |          |         | ≤-153     |           |           | 1710 MHz           |
| Input Power, r | maximum    | watt  |          |         | 50        |           |           |                    |
| Impedance      |            | ohm   |          |         | 50        |           |           |                    |

| MECHANICAL STUFF          |        |                                     |
|---------------------------|--------|-------------------------------------|
| Connector Type            |        | N-Female                            |
| Size                      | mm, in | 225 x 150, 8.86 x 5.90              |
| Packing Size              | mm, in | 210 x 210 x 110, 8.25 x 8.25 x 4.33 |
| Antenna Weight            | kg, lb | 45, 0.99                            |
| Operational Temperature   | °C, °F | -40 to 55, -40 to 131               |
| Radome Material and Color |        | ABS, White, RAL 9003                |
| Cable Length              | cm, in | 34, 13.38                           |
| Соах Туре                 |        | RG141                               |
|                           |        |                                     |



⊠ sales@boltontechnical.com www.boltontechnical.com

◎ 5010 Wright Road, Suite 115 Stafford, TX, 77477