

C1TAATO-E010PN-0000  
series\_t, Screw-Lock plug, mil\_standard\_38999



General information

|                   |                     |
|-------------------|---------------------|
| Part number       | C1TAATO-E010PN-0000 |
| Termination       | crimp               |
| Size              | 9 (STD 38999)       |
| Locking principle | screw               |
| Coding            | a_key_amc           |
| Cable Diameter    | cable_amc_t_e       |
| Cable outlet      | overmolding         |



CODING:A

POSITIONS: 10 positions

DIMENSIONS:

Contact insert description

|                    |           |
|--------------------|-----------|
| Number of contacts | 10        |
| Contact type       | pins      |
| Contact diameter   | 076mm     |
| Insulator material | peek      |
| Wire cross section | 22-26_awg |
| Termination        | crimp     |

Technical information

|                                |           |               |
|--------------------------------|-----------|---------------|
| Nominal current single contact | 05_a      | iec_60512_5_2 |
| Test voltage                   | 075_kv_ac | eia_364_20f   |

safety\_text

Mechanical and environmental data

|                       |              |
|-----------------------|--------------|
| Degree of protection* | ipsk8_ip6k9k |
| Operating temperature | 65_175_c     |
| Mating cycles         | 500          |

mated

Material and surface treatments

|         |                |
|---------|----------------|
| Housing | alu_tin_nickel |
| Contact | cu_alloy_gold  |

data\_text

safety\_text\_2

data\_text

ul\_text

illustrative\_text