CUSTOMER PRODUCT SPECIFICATION SHEET

RoHS Compliant


CAB556RF: I-PEX MHF 4L PLUG + SMA STRAIGHT BULKHEAD JACK + Ø1.13MM CABLE - 6GHz

SPECIFICATIONS:


- 1. I-PEX MHF 4L PLUG, P/N: 20565-001R-13.
- 2. Ø1.13MM COAXIAL CABLE, COLOR: BLACK
- 3. SMA STRAIGHT BULKHEAD JACK, GOLD PLATED, P/N: RFCT-SMA117-F13.

NOTES:


- 1. THE ORIENTATION OF CONNECTORS ON DRAWING IS FOR REFERENCE ONLY, IF THE ORDER IS LEFT BLANK THE CONNECTOR WILL NOT HAVE FIXED ORIENTATION.
- 2. FIXED ORIENTATION IS SUGGESTED FOR CABLE LENGTH 50MM TO 100MM. PLEASE SPECIFY THE FIXED ORIENTATIONS FROM THE ORDER CODE (F1, F2, ETC)
- 3. CONTACT GRAD CONN IF THE ORIENTATION YOU REQUIRE IS NOT SHOWN.
- 4. WORKING FREQUENCY RANGE: DC-6GHz.
- 5. OPERATING TEMPERATURE: -40°C TO +85°C
- 6. IMPEDANCE: 50 OHM








IPEX 4L PLUG DIMENSION



SMA JACK DETAIL DIMENSION



"L" LENGTH IN MM
eg: 100MM = 0100
(MIN. 0050, MAX. = 0400
STANDARD = 0100, 0150, 0200)
Tolerance: 50mm : ±2mm.
51–200mm: ±5mm.

201-400mm: ±7mm.

WASHER AND NUT OPTIONS:
BLANK = SEPERATELY PACKED (STANDARD)
A = ASSEMBLED WITH CONNECTOR

__CABLE SIZE:

 $1 = \phi 1.13MM$ CABLE, COLOR: BLACK

ORIENTATION OPTIONS:


HOW TO ORDER

CAB556RF - X X X X - X X - X - 1

BLANK = DOES NOT HAVE A FIXED ORIENTATION

F1 = MHF CONNECTION DOWN (L=50-200MM) F2 = MHF CONNECTION UP (L=50-200MM)

(SEE NOTES 1, 2, 3 AND DIAGRAMS FOR MORE INFORMATION)



RECOMMENDED SMA
MOUNTING HOLE

	Scale: NTS	THIRD ANGLE	Unstated .X .XX .XXX .XXX ANGLES	Tolerances: N/A N/A N/A N/A	Material
	Drawn: NYW	$\bigoplus \bigoplus$			SEE NOTE
	App'd: XXX	Title CABLE ASSEMBLY		NOT TO SCALE	
	Date: 7 APR. '23	Revision: 1.1		Unit: mm	



Drawing Number:
CAB556RF

Sheet 1 of 1