



JKL PART NO.: CF20305-24B

JKL LAMP PART NO.	COLOR WHITE	STARTING CIRCUIT VOLTAGE VS (Vrms)	OPERATING LAMP VOLTAGE VL (Vrms)	OPERATING LAMP CURRENT IL (mA rms)	BRIGHTNESS (CANDELA/m ²)	*RATED LIFE (HRS) (AVG.)
CF20305-24B	x = 0.278 ± 0.01 y = 0.264 ± 0.01	1750 @ 0°C	780	5	42,000 TYP.	40,000

* RATED LIFE IS DEFINED AS THE POINT AT WHICH THE INTENSITY BECOMES 50% OF THE INITIAL RATING.

<p>METRIC THIRD ANGLE PROJECTION</p>			<p>DIMENSIONS ARE IN MILLIMETERS</p> <p>TOLERANCE UNLESS OTHERWISE SPECIFIED</p> <p>1 PL +/- 0.2 2 PL +/- 0 ANGLE +/- 0</p>		<p>JKL COMPONENTS CORPORATION</p>					
<p>DRAWN BY L. WENGSTROM</p>			<p>APPVD BY DATE L.R. 8/28/07</p>		<p>SIZE A</p>	<p>FSCM NO. 55335</p>	<p>DRAWING NO. CF20305-24B</p>			
<p>START VOLTS TO 2600 & OPER. VOLT TO 1400</p>			<p>8/23/07</p>		<p>RELEASED 11/10/05</p>					
<p>DESCRIPTION/ECO NUMBER</p>			<p>APPVD DATE</p>		<p>SCALE NONE</p>		<p>RELEASED DATE 11/10/05</p>	<p>REVISION DATE 8/28/07</p>	<p>REV. NO. A</p>	<p>SHEET 1 OF 1</p>
<p>- CAD DRAWING - MANUAL REVISIONS NOT PERMITTED</p>										