



Technical Data Sheet

USB Type-C 7 Port Hub with 3 Type-C & 5 Type-A Ports w/DIN Rail – Surge Protection

Model Number: CG-7PU313C



USB 3.1 USB-C hub incorporates 5 USB Type-A and 2 USB-C reversible ports downstream and 1 USB-C Upstream port. This is a great hub choice for applications that need 5Gbps data speeds and multiple mounting options. It is backward compatible with USB 2.0/1.1 compliant host using its RISC-like USB controller. It provides a unique self-power mode to work with wide range (+7 ~ 48V DC) input DC power from its terminal block (power adapter sold separately).

Features

- Compliant with USB 3.1 Gen 1 Specifications
- Provides 1 USB3.1 Gen 1 Upstream Port with USB-C connector
- Supports 5Gbps, 480Mbps, 12Mbps and 1.5Mbps Speed
- Includes a Mounting bracket for flat surface mounting i.e. under desk, on walls or tech bench
- Supports Multi Transaction Translators per Hub
- Supports Wide Range Input (+7~48V DC) Self-power Mode from the Terminal Blocks
- Supports 15KV ESD Surge Protection for Each Port
- Supports a 2-pin Terminal Block Connector for external power input from AC adapter

Product Information

- **Model Number:** [CG-7PU313C](#)
- **Packing List:**
 - 7 Port USB 3.1 Hub
 - DIN Rail Mounting Clip and Screws
 - 3ft. USB 3.0 C to A USB 3.0 Cable
 - Surface Mounting Plate
 - Paper Installation Guide
- **Optional Accessories:** Does not include power supply.

Specifications

OVERVIEW

Product Type	USB 3.1 Hub (Backward compatible with USB 2.0/1.1)
Electrical Protections	15KV ESD Surge Protection
Mountable	Surface and DIN Rail Mounting (DIN Rail Clip Included)
Construction	Metal
Applications	Data Centers, Automotive peripheral installation, Machine Equipment, Kiosk, Office, and others
Certs / Compatibility	RoHS, CE, FCC, WEEE

CONNECTIONS

Type-A Downstream Ports	7 (5x USB-A ports and 2x USB-C ports)
Type-C Upstream Ports	1 (USB-C port)
7 ~ 48V Input Power	2-pin terminal block connector

AVAILABLE POWER MODES

Mode 1	Bus
Mode 2	Self power source (+7~48VDC from 2-pin terminal connector) Power Supply not included

ENVIRONMENTAL

Operating Temperature	0 to 55°C (32 TO 131°F)
Operating Humidity	5 to 95% RH
Storage Temperature	-20°C to 85°C (-4 to 185° F)

DIMENSIONS

Length	5.23" (13.30 cm)
Width	2.42" (6.15 cm)
Height	1.43" (3.63 cm)

OS SUPPORT

Windows	Windows 7, Windows 8, Windows 10
Other	Linux and Mac OS 10.X

LED

Power	1(green)
Downstream Ports	N/A

WARRANTY

Warranty Period	1 year from date of purchase
-----------------	------------------------------

PRODUCT URL

CG-7PU313C Product Page	https://www.coolgear.com/product/usb-c-7-port-hub-3x-type-c-5x-type-a-din-rail-surge-protection
-------------------------	---

© 2017 Coolgear, Inc. All Rights Reserved. All products and accompanying digital documentation including images are the property and / or trademarks of Coolgear Inc. Coolgear Inc. are continuously improving upon its products. Product specifications are subject to change without notice.