(5 : 1)











NOTES:

1. METALSHELLS: STEEL; min. 315µin TIN over 40-80µin NICKEL
2. INSULATORS: PA 6.6 UL 94 V-0, BLACK
3. FRAME: STEEL; NICKEL PLATED
4. FLOAT MOUNTS: COPPER ALLOY; NICKEL PLATED
5. RIVETED INSERTS: COPPER ALLOY; min. 200µin TIN over 80µin NICKEL
6. COLLARS: COPPER ALLOY; min. 200µin TIN over 80µin NICKEL
7. CONNECTOR IS PART MARKED: 16-507360 CONEC ABC

Directive 2002/95/EC RoHS compliant

THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC GmbH

DO NOT ALTER CAD DRAWING BY HAND

Customer Specific Product with special float frame

tolerance

dim. in mm

rev.	description	date	name
a	Original		

	date	name
drawn	21.03.13	Henneboel
appd.	22.03.13	Fischer
norm		
d-old		

scale: 2:1 (5:1)

material: SEE NOTES

title:

D- SUB HD FEMALE

78pos. CRIMP STYLE

with frame, float for blind mating system

dwg no: 16K1A3208

DIN-A3

sh: 1

part no: 16-507360