© 2023 TE Connectivity. All Rights Reserved.

REVISIONS					
P	LTR	DESCRIPTION	DATE	DWN	APVD
	J	ECN-23-227208; DRW REG W/CREO	08AUG2023	DR	JHW







NOTES:

1. MATES WITH TEC P/N 212013-1 IN AMPLIMITE CONNECTOR ASSEMBLIES ONLY

2. APPROVED CRIMP TOOLING: DANIELS CRIMP TOOL P/N FT8, DANIELS POSITIONER P/N TP731,
   STRIP LENGTH = .375 [9.53], #16 AWG SETTING 8, #18 AWG SETTING 6.
   NOTE: USE OF ANY UNAPPROVED TOOLING WILL RESULT IN CRIMPED TERMINATIONS THAT ARE NOT QUALIFIED

3. WIRE BARREL ACCEPTS #16 -#18 AWG STRANDED WIRE

△4 RETENTION CLIP DIAMETER TO BE MEASURED WITH RING GAGE

5. FINISH:
   CONTACT: GOLD PLATE .000050 [.00127] MIN THK PER ASTM-B-488 OVER
   NICKEL UNDERPLATE .000050 [.00127] MIN THK PER PER QQ-N-290
   RETENTION CLIP: NICKEL PLATE .000050 [.00127] MIN THK PER PER QQ-N-290

△6 RESTRICTED PART NUMBER

△6 1-212014-1
212014-2
212014-1
PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS: IN [MM]

TOLERANCES UNLESS OTHERWISE SPECIFIED:
0 PLC ±-
1 PLC ±-
2 PLC ±-
3 PLC ±.005 [0.13]
4 PLC ±-
ANGLES ±-

MATERIAL -
-

FINISH -
-

DWN C.C.THOMAS 10NOV2000
CHK D.MILLER 10NOV2000
APVD D.MILLER 10NOV2000

PRODUCT SPEC -
APPLICATION SPEC -
WEIGHT -

TE Connectivity

NAME CONTACT ASSY, SOCKET CRIMP
TYPE, SIZE 8, WIRE SIZE 16-18 AWG
-

SIZE	CAGE CODE	DRAWING NO	RESTRICTED TO
A1	00779	C-212014	-

CUSTOMER DRAWING | SCALE 10:1 | SHEET 1 OF 1 | REV J