© 2021 TE Connectivity. All Rights Reserved.

REVISIONS					
P	LTR	DESCRIPTION	DATE	DWN	APVD
	A	REVISED PER ECN-22-148284	09APR2022	WH	LC









RECOMMENDED PCB LAYOUT
TOLERANCE: ±0.05

1. MATERIAL:
   HOUSING:HIGH PERFORMANCE RESIN,UL94-V0 COLOR: NATURAL
   PIN CONTACT: COPPER ALLOY, 2.0µm MIN TIN OVERALL
2. DIMENSIONS SHOWN REPRESENT PRODUCT IN DRY, AS MOLDED, CONDITION.
3. RECOMMENDED MATING PART:[ ]-2377130-[ ]
4. PACKAGING: LOOSE PIECE

2375267-8 SHOWN

DIM C	DIM B	DIM A	POSITION	PART NO.
39.60	41.00	43.50	11	1-2375267-1
35.64	37.04	39.54	10	1-2375267-0
31.68	33.08	35.58	9	2375267-9
27.72	29.12	31.62	8	2375267-8
23.76	25.16	27.66	7	2375267-7
19.80	21.20	23.70	6	2375267-6
15.84	17.24	19.74	5	2375267-5
11.88	13.28	15.78	4	2375267-4
7.92	9.32	11.82	3	2375267-3
3.96	5.36	7.86	2	2375267-2

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS: mm

TOLERANCES UNLESS OTHERWISE SPECIFIED:
0 PLC ±
1 PLC ±0.5
2 PLC ±0.30
3 PLC ±
4 PLC ±
ANGLES ±3

MATERIAL 1

FINISH 1

DWN W. HUO 04FEB2022
CHK L. CHEN 07FEB2022
APVD D. ZHANG 07FEB2022
PRODUCT SPEC 108-2297
APPLICATION SPEC 114-13265
WEIGHT -

TE Connectivity

NAME HEADER ASSEMBLY, UNSHROUDED VERTICAL, SINGLE ROW, EP3.96

SIZE	CAGE CODE	DRAWING NO	RESTRICTED TO
A2	00779	C-2375267	-

CUSTOMER DRAWING | SCALE N/A | SHEET 1 OF 1 | REV A