



Mobile Coil Antennas

Elastomer Spring Packages

Premium mobile load coil antennas are industry standard

Our ongoing commitment to refinement in mechanical and electrical design has resulted in the release of our latest product, the mobile coil antenna with an elastomer spring. The new elastomer spring provides increased flexibility, better shape retention, and eliminates electronic noise & road noise compared to stainless steel springs. The mobile coil antennas will continue to maintain all of the features that make them unique, such as stainless steel whips, housings constructed with ABS material injection molded around a solid brass insert, and gold plated push pin contacts. Together, the mobile coil antenna and elastomer spring, make these products the obvious choice for quality and long lasting value for demanding mobile radio communications.

ORDERING INFORMATION

BASE ANTENNA	ANTENNA W/ ELASTOMER SPRING PN	DESCRIPTION	GAIN
B1322N	B1322NR	132 - 174 MHz Chrome, NGP, Elast Spr	2 dBi
	BB1322NR	132 - 174 MHz Black, Elast Spr	2 dBi
B1323-L	B1323R	132 - 174 MHz Chrome, Elast Spr	3 dBi
	BB1323R	132 - 174 MHz Black, Elast Spr	3 dBi
B1442N	B1442NR	144 - 174 MHz Chrome, NGP, Elast Spr	2 dBi
	BB1442NR	144 - 174 MHz Black, NGP, Elast Spr	2 dBi
B1443-L	B1443R	144 - 174 MHz Chrome, Elast Spr	3 dBi
	BB1443R	144 - 174 MHz Black, Elast Spr	3 dBi
B4502N-L	B4502NR	450 - 470 MHz Chrome, NGP, Elast Spr	2 dBi
B4503-L	B4503R	450 - 470 MHz Chrome, Elast Spr	3 dBi
	BB4503R	450 - 470 MHz Black, Elast Spr	3 dBi
B4505C	BB4505CR	450 - 470 MHz Black, Elast Spr	5 dBi
B7603-L	BB7603R	760 - 870 MHz Chrome, GP, Elast Spr	3 dBi
B8965CN	B8965CNR	896 - 970 MHz Chrome, NGP, Elast Spr	5 dBi
Replacement Elastomer Springs	SRS-062-C-001	Replacement Rubber Spring, 0.062" Rod Diameter	
	SRS-100-C-001	Replacement Rubber Spring, 0.100" Rod Diameter	
	SRS-125-C-001	Replacement Rubber Spring, 0.125" Rod Diameter	

ENVIRONMENTAL SPECIFICATION

Operating Temp	-45 to 85°C
Storage Temp	-45 to 85°C
Wind Speed Survivability	100 mph+
Cold	-45
Heat	85
Temperature Shock	N/A
Humidity	85% @ 85°C
Rain / Ingress	N/A (IP67 targeted spec/standard)
Salt Fog	N/A
Flammability	N/A
Vibrations	N/A



DIMENSIONAL SPECIFICATION

Height	65-85 mm Depends on Whip OD options
Base OD	22 mm
Installation Threads	5/16--24
Whip Diameter	0.100", 0.062" & 0.125" Options
Whip Lock	Dual Set Screw
Nut Size	23 mm hex

MATERIALS SPECIFICATION

Body Material	EPDM Rubber
Ferrule Material	Chrome Plated Brass

VHF - STAINLESS STEEL VS. ELASTOMER SPRING



TE TECHNICAL SUPPORT CENTER

USA:	+1 (800) 522-6752
Canada:	+1 (905) 475-6222
Mexico:	+52 (0) 55-1106-0800
Latin/S. America:	+54 (0) 11-4733-2200
Germany:	+49 (0) 6251-133-1999
UK:	+44 (0) 800-267666
France:	+33 (0) 1-3420-8686
Netherlands:	+31 (0) 73-6246-999
China:	+86 (0) 400-820-6015

te.com

TE, and TE connectivity (logo) are trademarks owned or licensed by the TE Connectivity Ltd. family of companies. All other logos, products and/or company names referred to herein might be trademarks of their respective owners.

The information given herein, including drawings, illustrations and schematics which are intended for illustration purposes only, is believed to be reliable. However, TE Connectivity makes no warranties as to its accuracy or completeness and disclaims any liability in connection with its use. TE Connectivity's obligations shall only be as set forth in TE Connectivity's Standard Terms and Conditions of Sale for this product and in no case will TE Connectivity be liable for any incidental, indirect or consequential damages arising out of the sale, resale, use or misuse of the product. Users of TE Connectivity products should make their own evaluation to determine the suitability of each such product for the specific application.

TE Connectivity warrants to the original end user customer of its products that its products are free from defects in material and workmanship. Subject to conditions and limitations TE Connectivity will, at its option, either repair or replace any part of its products that prove defective because of improper workmanship or materials. This limited warranty is in force for the useful lifetime of the original end product into which the TE Connectivity product is installed. Useful lifetime of the original end product may vary but is not warranted to exceed one (1) year from the original date of the end product purchase.

©2022 TE Connectivity. All Rights Reserved.

08/22 Original