



Note: parts in bulk,
100SET/bag

ELECTRIC CHARACTERISTICS REQUIREMENTS:

1. Product must be 100% conduction, open circuit short circuit test.
2. Conductive resistance: 20Ω
3. Rated voltage: AC 60V
4. Withstand voltage: AC 200V
5. Insulation resistance: $500m\Omega$
6. Characteristic impedance: 50Ω
7. Adopt environmental protection process and meet ROHS requirements
8. Tensile test: 1.5kg~
9. The general tolerance shall prevail if no tolerance is noted

RoHS Compliant

ITEM	PART No.	VENDOR	DESCRIPTION	Q'TY	OVERALL WIRE LENGTH
5	COVER	-	RED HAT PACKING SMA	1	-
4	SMA FEMALE	-	11*1.13-ZYK-BACK PLUG RIVETING AND GOLD PLATING	1	-
3	HEAT SHRINK SLEEVE	-	2.0*18MM BLACK HEAT SHEINK SLEEVE	1	-
2	IPEX-1.13 CONN	-	IPEX-1.13 BRASS GOLD	1	-
1	COAXIAL CABLE	-	RG1.13 DARK GREY-48-TIN-FEP JACKET L=155MM	1	155
MATERIAL SPECIFICATION					

SYM	NAME	DATE	REVISIONS	DRAWN BY	CHECKED BY	APPROVED BY	CONFIRMED BY	DESCRIPTION	CviLux Corporation		CUST. CODE
				LuLu	Iron	Iron	Waleed	RF CABLE	瀚荃股份有限公司 CviLux Corporation		CUC
				08/21.20'	08/21.20'	08/21.20'	08/21.20'	SHEET: 1 OF 1	DRAWING No.	CviLux P/N	CUSTOMER P/N
									DH50625A	DH-20G50011	-