

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18

STANDARD EXECUTIONS

- **DVA.7:** bushing with threaded blind hole and base plate in polished zinc-plated steel, vibration-damper body in natural rubber NR, black colour, hardness 40, 55, 70 Shore A ± 5 .
- **DVA.7-SST:** bushing with threaded blind hole and base plate in AISI 304 stainless steel, vibration-damper body in natural rubber NR, black colour, hardness 55 Shore A ± 5 .

FEATURES AND APPLICATIONS

The rubber buffers have been designed to damp vibrations, shocks and noises produced by moving bodies or non-balanced vibrating masses of equipment and machines which can cause:

- malfunctioning and reduction of the machine lifespan and/or of the adjacent ones;
- damage to health;
- noise.

Load diagrams for each single code are available on request. See Technical data and guidelines for the choice(on page 728).


SPECIAL EXECUTIONS ON REQUEST

Natural rubber NR, hardness 40, 70 tolerance ± 5 Shore A for executions with AISI 304 stainless steel base.



* Complete the description with the desired hardness: 40, 55 or 70 tolerance ±5 Shore A.

DVA.7




DVA.7 - 20 - 24 - M6 - 55
 D L d Shore A

Conversion Table					
1 mm = 0.039 inch					
D		L			
mm	inch	mm	inch	mm	inch
10	0.39	10	0.39	58	2.28
20	0.79	15	0.59	61	2.40
25	0.98	20	0.79	68	2.68
30	1.18	24	0.94	89	3.50
35	1.38	30	1.18		
50	1.97	36	1.41		
70	2.76	40	1.57		
75	2.95	50	1.97		

METRIC

Description	D	L	d	h	△	Hardness 40 Shore A			Hardness 55 Shore A			Hardness 70 Shore A					
						Code	Max load [N]	Max deflection [mm]	Stiffness [N/mm]	Code	Max load [N]	Max deflection [mm]	Stiffness [N/mm]	Code	Max load [N]	Max deflection [mm]	Stiffness [N/mm]
DVA.7-10-10-M5*	10	10	M5	5	2	416271	46	3	14	413571	59	3	20	418971	113	3	40
DVA.7-20-15-M6*	20	15	M6	6	7	416297	84	5	17	413597	194	4	48	418997	321	4	78
DVA.7-20-24-M6*	20	24	M6	6	8	416301	82	6	14	413601	130	6	22	419001	330	6	55
DVA.7-25-20-M6*	25	20	M6	6	15	416307	84	5	17	413607	190	5	38	419007	495	5	96
DVA.7-30-30-M8*	30	30	M8	8	28	416311	190	8	25	413611	260	8	35	419011	630	8	84
DVA.7-30-36-M8*	30	36	M8	8	30	416321	180	9	20	413621	320	9	36	419021	650	9	72
DVA.7-35-40-M8*	35	40	M8	8	43	416331	260	10	26	413631	300	10	30	419031	630	10	63
DVA.7-50-50-M10*	50	50	M10	10	100	416337	481	13	38	413637	835	13	67	419037	1147	13	92
DVA.7-50-61-M8*	50	61	M8	8	114	416341	490	15	32	413641	600	15	39	419041	1520	15	100
DVA.7-50-68-M10*	50	68	M10	10	120	416351	490	17	29	413651	890	17	52	419051	1950	17	115
DVA.7-70-58-M12*	70	58	M12	12	230	416371	890	15	61	413671	1390	15	96	419071	1923	15	133
DVA.7-75-89-M12*	75	89	M12	12	373	416381	971	22	44	413681	1675	22	75	419081	2328	22	105

DVA.7-SST



DVA.7 - 20 - 24 - SST - M6 - 55
 D L Stainless steel d Shore A

INOX STAINLESS METRIC

Description	D	L	d	h	△	Hardness 40 Shore A			Hardness 55 Shore A			Hardness 70 Shore A					
						Code	Max load [N]	Max deflection [mm]	Stiffness [N/mm]	Code	Max load [N]	Max deflection [mm]	Stiffness [N/mm]	Code	Max load [N]	Max deflection [mm]	Stiffness [N/mm]
DVA.7-10-10-SST-M5-55	10	10	M5	5	2		46	3	14	410581	59	3	20		113	3	40
DVA.7-20-15-SST-M6-55	20	15	M6	6	7		84	5	17	410597	194	4	48		321	4	78
DVA.7-20-24-SST-M6-55	20	24	M6	6	8		82	6	14	410601	130	6	22		330	6	55
DVA.7-25-20-SST-M6-55	25	20	M6	6	15		84	5	17	410606	190	5	38		495	5	96
DVA.7-30-30-SST-M8-55	30	30	M8	8	28	ON REQUEST	190	8	25	410611	260	8	35	ON REQUEST	630	8	84
DVA.7-30-36-SST-M8-55	30	36	M8	8	30		180	9	20	410613	320	9	36		650	9	72
DVA.7-35-40-SST-M8-55	35	40	M8	8	43		260	10	26	410621	300	10	30		630	10	63
DVA.7-50-50-SST-M10-55	50	50	M10	10	100		481	13	38	410627	835	13	67		1147	13	92
DVA.7-50-61-SST-M8-55	50	61	M8	8	114		490	15	32	410631	600	15	39		1520	15	100
DVA.7-50-68-SST-M10-55	50	68	M10	10	120		490	17	29	410633	890	17	52		1950	17	115
DVA.7-70-58-SST-M12-55	70	58	M12	12	230		890	15	61	410651	1390	15	96		1923	15	133
DVA.7-75-89-SST-M12-55	75	89	M12	12	373		971	22	44	410661	1675	22	75		2328	22	105

Vibration damping elements