

## CAT-3 • CAT-3-R16 • CAT-3-R18

The CAT-3-CHUCK Rewinder Series affords the fastest loading and unloading of cores and label rolls, and is ideal for high-volume production environments, label slitting applications, or anywhere the ultimate convenience in Rewinders is desired.



**CAT-3-CHUCK-220**

Technical Specifications	CAT-3	CAT-3-R16	CAT-3-R18
<b>Max Roll Diameter (in)</b>	12 (305-mm)	16 (406-mm)	18 (457-mm)
<b>Core Diameter (in)</b>	3 (76-mm)		
<b>Max Media Width (in) <sup>1</sup></b>	6 - 10 (152 - 254-mm)		
<b>Max Roll Weight (lbs)</b>	20 (9-kg)	32 (14.5-kg)	50 (22-kg)
<b>Dimensions-HWD (in)</b>	14x12x17 (355 x 305 x 432-mm)	19x16x17 (482 x 406 x 432-mm)	20x18x19 (508 x 457 x 482-mm)
<b>Weight (lbs) <sup>1</sup></b>	28 - 30 (12.7 - 13.6-kg)	30 - 32 (13.6-kg - 14.5-kg)	34 - 36 (15.4 - 16.3-kg)
<b>Max Speed (ips)</b>	240 (6096-mm)	320 (8128-mm)	360 (9144-mm)
<b>Min Speed (ips)</b>	0.5 (13-mm)		
<b>Max Torque (in-oz) <sup>2,3</sup></b>	183	228	228
<b>Max RPM <sup>2</sup></b>	388	485	
<b>Number of Flanges</b>	2		
<b>Power Specifications</b>	120 - 220VAC in, 12VAC 40W Out <sup>1</sup>	120 - 220VAC in, 19VDC 80W Out	
<b>Warranty</b>	5 year limited warranty on Rewinder - 1 year limited warranty on Power Adaptor		
<b>Available Options</b>	<ul style="list-style-type: none"> <li>• HTO-CAT (Hi-Torque Option)</li> <li>• LTO-CAT (Lw-Torque Option)</li> <li>• ADAPT-326 (6" Core Adaptor)</li> <li>• FOOTSWITCH</li> </ul>	<ul style="list-style-type: none"> <li>• LTO-CAT (Lw-Torque Option)</li> <li>• ADAPT-326 (6" Core Adaptor)</li> <li>• FOOTSWITCH</li> </ul>	<ul style="list-style-type: none"> <li>• LTO-CAT (Lw-Torque Option)</li> <li>• ADAPT-326 (6" Core Adaptor)</li> <li>• FOOTSWITCH</li> </ul>

1. Depends on whether you order the CHUCK, CHUCK-220, or CHUCK-10 model

2. **HTO-CAT** increases Max Torque to 228 in-oz, Max RPM to 485, 304 ips (7,721-mm), and Power Out to 19VDC 80W.

3. **LTO-CAT** decreases Torque Range to 172 - 35 in-oz.