

CONNECT

We realize ideas

P | Cabling

Data sheet

Flush mounted built-in outlet gray

Page 1/3

P/N 1309441903-I EAN 4015394048176

> 2023/04/24 Version: C

Illustrations



See enlarged drawings at the end of document

Product specification

• UP installation outlet for flush mounting of the IP44SG UP housing







P | Cabling

Data sheet Flush mounted built-in outlet gray

We realize ideas

P/N 1309441903-I EAN 4015394048176

> 2023/04/24 Version: C

Page 2/3

	version: C
Technical Data	
General Data	
Fields of application	office areas
Mechanical measurement according to MICE	M1
Ingress measurement according to MICE	I1
Climatic measurement according to MICE	C1
Electromagnetic measurement according to MICE	E3
Design	wall outlet
Mounting style	UP
Color	gray
Materials and material properties	
Halogen free	yes
RoHS	compliant
Environmental conditions	
Particulate ingress	IP4X
Liquid ingress/immersion	IPX4
Standards/Regulations	
Cover plates for installation devices 1	DIN 49075-1:1989-10
Cover plates for installation devices 2	DIN 49075-2:1989-10
Classifications	
ETIM 5.0	EC000766
ETIM 6.0	EC000766
ETIM 7.0	EC000119
ETIM 8.0	EC000119
ETIM 9.0	EC000119
Packing details	
Type of packaging	1 pc(s) / plastic bag
Packaging unit - Weight (gram)	762 g
Packaging unit - Weight (pound)	1.68 lb
Packaging dimension	300 mm x 200 mm x 50 mm
Packaging dimension	11.811 in. x 7.874 in. x 1.969 in.







P | Cabling

We realize ideas

Data sheet Flush mounted built-in outlet gray

Page 3/3

P/N 1309441903-I

EAN 4015394048176

2023/04/24 Version: C

Accessories from

P/N	Designation
1309461002-I	E-DAT modul IP44SG flush mounted housing pure white unequipped
1309461003-I	E-DAT modul IP44SG flush mounted housing gray unequipped



