



- Wireless Receiver/Gateway with LAN Output (Ref: BeanGateway[®] Indoor)
- Windless inclusion the second and have recommended with the second secon
- Wireless inclinometer sensor with standard base, measurement range ±30° (ref: BeanDevice® 2.4GHZ INC

±30 degree)

BeanAir

- Free software to collect and display in real-time data measurement from the vibration sensor (Ref: BeanScape[®] 2.4GHZ version)
- AC/DC Power Adapter (US or EUR or UK plugs) for charging the battery or to be used constantly



MAIN FEATURES

- Wireless Inclinometer sensor (measurement range ±30°)
- Global License-free band 2.4GHZ, with maximum radio range 650 meters
- Extremely precise Inclinometer (±0.006° of precision)
- Time-synchronized data acquisition (±2.5ms of accuracy)
- Waterproof IP67 aluminum casing (Nema 6)
- Rechargeable Lithium-Polymer battery 2200 mAh providing a battery life up to 15 months
- Embedded data logger : up to 1 million data points (with events dating)

Beanair products are Made in Germany and are certified CE/FCC/Giteki

WEBLINKS TO PRODUCTS

- Wireless Inclinometer Sensor
- Wireless Receiver/Gateway
- Eco-friendly Monitoring Software

HOW IT WORKS ?

BeanScape[®] 2.4GHz Wireless IOT Supervision Software



2

BeanAir STARTERKIT

WIRELESS IOT INCLINOMETER SENSOR

CONTACT US

| Headquarter: | Email: | Phone number: |
|---|------------------|-----------------|
| BeanAir GmbH Wolfener Straße 32 - 34 12681 Berlin | info@beanair.com | +49 30 98366680 |
| | www.beanair.com | |
| | | |
| | | |