

## SUMMARY

### # Wires

Low voltage 36



*Image is for illustrative purpose only*

Series	1R
Termination type	Female crimp
IP rating	50
AWG wire size	26.00 - 22.00
Cable Ø	2.00 - 9.20 mm
Status	Active
Matching parts	<a href="#">FGG.1R.336.GLC92</a>

### Download

[Request a quote](#)

[Catalog](#)

## TECHNICAL DETAILS

### Mechanics

Shell Style/Model	EGG*: Fixed receptacle, key (G) or key (A)
Keying	3 keys (alpha=50,beta=30, plug: male contacts, receptacle: female contacts)
Housing Material	Crastin® PBT (Polybutylene terephthalate), gray
Weight	13.44 g

### Performance

Configuration	1R.336 : 36 low voltage
Insulator	L: PEEK (UL 94 / V-0/1.5)
Rated Current	2.5 Amps


### Specifications

Contact Type: Crimp  
Test voltage (kV rms) Contact-contact: 1.5

### Others

*LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.*

# DRAWINGS



## Dimensions

	A	B	L	M
mm.	37	12.5	18	14.5
in.	1,46	0,49	0,71	0,57

# RECOMMENDED BY LEMO

## Tools

- Crimp Tool: [DPC.91.701.V](#)  
Crimp settings: AWG/Selector = 22-24-26/6-5-5  
Positionner: [DCE.91.070.BVM](#)  
Extractor: [DCC.07.04B.LAG](#)  
Replacement contact: EGG.0B.655.ZZM

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.