

SUMMARY

Wires

Low voltage 2



Image is for illustrative purpose only

Series	5K
Termination type	Male solder
IP rating	68 mated (mating interface)
AWG wire size	16.00 - 8.00
Cable Ø	12.60 - 13.50 mm
Status	Active
Matching parts	EGG.5K.302.CLL

Download

[Request a quote](#)

[Eplan](#)

[Catalog](#)

TECHNICAL DETAILS

Mechanics

Shell Style/Model	FG*: Straight plug, cable collet
Keying	1 key (alpha=0, plug: male contacts, receptacle: female contacts)
Housing Material	Brass (chrome plated [SAE AMS 2460]) shell, collet nut and latch sleeve, nickel plated [SAE AMS QQ N 290] brass mid pieces
Weight	429.64 g

Performance

Configuration	5K.302 : 2 Low Voltage
Insulator	L: PEEK (UL 94 / V-0/1.5)
Rated Current	50 Amps

Specifications


Contact Type:	Solder
Contact Dia.:	6 mm (0.236in)
Bucket Dia.:	5.2 mm (0.205in)
Max. Solid Conductor:	10 mm ² (AWG 8)
Max. Stranded Conductor:	10 mm ² (AWG 8)
R (max):	1.2 mOhm
Vtest (contact-shell):	2950 V (AC), 4170 V (DC)
Vtest (contact-contact):	3600 V (AC), 5090 V (DC)

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

Others

Endurance (Shell): 5000 mating cycles
Temp (min / max): -55°C / +200°C
Humidity (max): <=95% [at 60 deg C / 140 F]
Vibration: 15 g [10 Hz - 2000 Hz]
Shock Resistance: 100 g [6 ms]
Climatical Category: 50/175/21
Shielding (min): 95 dB (10 MHz)
Shielding (min): 80 dB (1 GHz)
Salt Spray Corrosion: >1000 hr

DRAWINGS



Dimensions

	A	L	M	S2
mm.	38	92	67	30
in.	1,50	3,62	2,64	1,18

RECOMMENDED BY LEMO

Tools

Caps: [BFG.5K.100.NAS](#)

LEMO products and services are provided “as is”. LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.