


Flared Vinyl Insulated Butt Connectors

Material: Tin Plated Copper
Maximum Electrical Rating: 75°C, 600V
Insulation Material: Vinyl




T = Material Thickness

HOFFMAN PART NO.	WIRE SIZE	BARREL TYPE	AMPS	DIMENSIONS (INCHES)					UL	TAPE MOUNTED REEL QTY	DIE FOR TAPE MOUNTED	HAND TOOL
				L	D	d1	T					
FVC2216WS	22-16	Butted Seam	9-18	.969	.157	.067	.031	Y	1000	3V2216		
BUTR	22-16	Butted Seam	9-18	.945	.110	.067	.029	N	NA	NA		
FVC2216	22-16	Tubular	9-18	.953	.157	.067	.031	Y	1000	3V2216		
FVC1614WS	16-14	Butted seam	18-30	.969	.177	.091	.031	Y	1000	3V1614	YNM2210	
BUTB	16-14	Butted Seam	18-30	.984	.145	.091	.029	N	NA	NA		
FVC1614	16-14	Tubular	18-30	.953	.177	.091	.031	Y	1000	3V1614		
FVC1210WS	12-10	Butted Seam	35-50	1.043	.248	.134	.039	Y	500	3V1210		
BUTY	12-10	Butted Seam	35-50	1.080	.205	.134	.029	N	NA	NA		
FVC1210	12-10	Tubular	35-50	1.024	.248	.134	.039	Y	500	3V1210		
FVC8R1	8	Butted Seam	70	1.398	.335	.177	.047	Y	NA	NA	YNM86	
FVC6R1	6	Tubular	95	1.772	.413	.232	.059	Y	NA	NA	YNM86	

Straight Nylon Insulated Butt Connector

Material: Tin Plated Copper
Maximum Electrical Rating: 105°C, 600V
Insulation Material: 6/6 Nylon



T = Material Thickness

HOFFMAN PART NO.	WIRE SIZE	BARREL TYPE	AMPS	DIMENSIONS (INCHES)					UL	TAPE MOUNTED REEL QTY	DIE FOR TAPE MOUNTED	HAND TOOL
				L	D	d1	T					
NC2622	26-22	Tubular	5.5 - 9	.787	.079	.051	.031	N	NA	NA	YNT2622	
NC2622/J	26-22	Tubular	5.5 - 9	.787	.079	.047	.031	Y	NA	NA	YNT2622	
NC2216	22-16	Tubular	9 - 18	1.075	.126	.067	.031	Y	1000	3V2216	YNM2210	
NCL2216	22-16	Brazed Seam	9 - 18	1.075	.126	.067	.031	Y	NA	NA	YNM2210	
NCL2216/J	22-16	Tubular	9 - 18	.894	.154	.067	.031	Y	NA	NA	YNT2216	
NC1614	16-14	Tubular	18 - 30	1.075	.150	.091	.031	Y	1000	3V1614	YNM2210	
NCL1614	16-14	Brazed Seam	18 - 30	1.075	.150	.091	.031	Y	NA	NA	YNM2210	
NC1210	12-10	Tubular	35 - 50	1.075	.209	.134	.031	Y	500	3V1210	YNM2210	
NCL1210	12-10	Brazed Seam	35 - 50	1.075	.209	.134	.031	Y	NA	NA	YNM2210	

