Roller central guides

Technopolymer, aluminium, stainless steel













PROFILE

Anodised aluminium, natural colour, matte finish.

PINS SUPPORT

Acetal resin based (POM) technopolymer, white colour.

PINS

AISI 304 stainless steel.


ROLLERS

Polyethylene based (PE) technopolymer, grey colour.

STANDARD EXECUTIONS



- GCA-4-RS: with shaped rollers, spherical contact.
- GCA-4-RC: with cylindrical rollers.
- GCA-4-RT: with shaped rollers, cylindrical contact.



GCA-4 central guides are self-supporting structures for the side guide of products with important vertical dimensions on conveyor belts (Fig.1).



- GCA-4-RS: for the guide of products in cans or in plastic containers;
- GCA-4-RC: for the guide of cardboard products, for a greater fluency;
- GCA-4-RT: for the guide of glass products, in case of accidental breakage they facilitate the expulsion of debris.

Supplied assembled in bars of 1440 or 3000 mm length.


SPECIAL EXECUTIONS ON REQUEST


- Central guides with rollers in different colours.
- Central guides with pins in acetal resin based (POM) technopolymer.


ACCESSORIES ON REQUEST


- BDG: zinc-plated steel connecting bar for guides.
- TGL: closing cap for guides.
- PGC-4: separation block for central guide.
- MPG-P: assembly pin.
- MPG-V: zinc-plated steel hammer head screw. (see GLA-1).











GCA-4-RS		ME	TRIC
Code	Description	L	Δ'Δ
419134	GCA-4-RS-103-1440	1440	6260
/10131	GCA 4 PS 103 3000	3000	13040

GCA-4-RC

7071 T 110				
Code	Description	L	Δ'Δ	
419135	GCA-4-RC-103-1440	1440	6260	
419132	GCA-4-RC-103-3000	3000	13040	

GCA-4-RT

GCA-4-RT INOX STAINLESS STEEL METRIC					
Code	Description	L	$\nabla_{\!$		
419136	GCA-4-RT-103-1440	1440	6260		
419133	GCA-4-RT-103-3000	3000	13040		





METRIC

1