



specifications

| Consumption     | Voltage     | CRI | Base      | Lens                  | Heat Sink | L70 hours | Ambient Temp (F) | Power Factor | Mounting              | THD  | Beam Angle | Enclosed Fixture Rated |
|-----------------|-------------|-----|-----------|-----------------------|-----------|-----------|------------------|--------------|-----------------------|------|------------|------------------------|
| 24W<br>3 strips | ⚡ 100-277 V | 83  | hard-wire | frosted polycarbonate | aluminum  | 50,000    | -4 - 104°        | >0.9         | magnetic strip screws | <25% | 120°       | yes                    |

\*select your lamp

| Part Number        | Color Temp | Dimmable | Efficacy     | Lumens  |
|--------------------|------------|----------|--------------|---------|
| GI-23TRK-W50DC-UL4 | 3000K ⚡    | 0-10 V   | 132.7 lm / w | 3,184.3 |
| GI-23TRK-W50C-UL4  | 3500K ⚡    | no       | 132.7 lm / w | 3,184.3 |
| GI-23TRK-D50C-UL4  | 4000K ⚡    | no       | 132.7 lm / w | 3,184.3 |
| GI-23TRK-C50C-UL4  | 5000K ⚡    | no       | 132.7 lm / w | 3,184.3 |

other

| Dimensions | Warranty | Case QTY |
|------------|----------|----------|
| 2 ft       | 6 years  | 30 pcs   |



included driver



Features

- ▶ Does not need tombstones; hard-wired
- ▶ 50,000 hour LED lifespan based on IES LM-80 results and TM-21 calculations
- ▶ External driver
- ▶ Can be installed using included screws or magnetic backing



Not all product variations listed on this page may be DLC qualified. Visit [www.designlights.org/search](http://www.designlights.org/search) to confirm qualification.

