






## General information

|                   |                     |
|-------------------|---------------------|
| Part number       | GK2YAR-P16UC00-000L |
| Termination       | pcb                 |
| Size              | 2                   |
| Locking principle | break , push        |
| Coding            | a_key.amc           |
| Cable Diameter    | cable amc_2         |



### Contact insert description

|                      |         |
|----------------------|---------|
| Number of contacts   | 16      |
| Contact type         | sockets |
| Contact diameter     | 05mm    |
| Insulator material   | peek    |
| Termination          | pcb     |
| Termination diameter | 05mm    |
| Data transmission    | hdmi_13 |

reverse gender on request

### Connection diagram

con hdmi 13

## Technical information

|                                |          |               |
|--------------------------------|----------|---------------|
| Nominal current single contact | 05_a     | iec_60512_5_2 |
| Nominal current insert         | 2.5 A    | vde_0298_4    |
| Test voltage                   | 12_kv_ac | eia_364_20f   |

safety text

Mechanical and environmental data

|                       |              |
|-----------------------|--------------|
| Degree of protection* | ipsk8_ip6k9k |
| Operating temperature | 51_125_c     |
| Mating cycles         | 5000         |

mated

Material and surface treatments

|         |               |
|---------|---------------|
| Housing | ruthenium     |
| Contact | cu_alloy_gold |

data\_text

safety\_text\_2  
data\_text  
ul\_text  
illustrative\_text