

# GMA.0B.045.RB

## SUMMARY

#### # Wires



Image is for illustrative purpose only

Series	OB	
Termination type	No contacts / Accessory	
IP rating	0	
AWG wire size	0.00 - 0.00	
Cable Ø	4.50 - 5.20 mm	
Status	Active	

#### Download

Request a quote Catalog

# **TECHNICAL DETAILS**

#### **Mechanics**

Shell Style/Model	GMA*: Bend relief White
Keying	No keying
Housing Material	Silicone elastomer VMQ
Variant	B : White
Weight	.47 g

#### Performance


Configuration Insulator Rated Current

#### Others

Temp (min / max): -60°C / +200°C Temperature range in water steam: +140°C

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

### DRAWINGS



No keying

#### Dimensions

	А	L
mm.	4.5	27
in.	0,18	1,06

### **RECOMMENDED BY LEMO**

Tools

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.