



**Metric table**

Dimensions in: millimeters - inches

d <sub>1</sub>	d <sub>2</sub> Thread		Length l		b	h <sub>1</sub>		h <sub>2</sub>	t
	1	2	3			GB1	GP1		
30 <i>1.18</i>	M 4	M 5	15 <i>.59</i>	-	13 <i>.51</i>	15 <i>.59</i>	11 <i>.43</i>	4 <i>.16</i>	9 <i>.35</i>
30 <i>1.18</i>	M 6	M 8	15 <i>.59</i>	25 <i>.98</i>	13 <i>.51</i>	15 <i>.59</i>	11 <i>.43</i>	4 <i>.16</i>	9 <i>.35</i>

**Specification**

- Wing body  
Nylon plastic  
- Glass filled  
- Temperature resistant up to 230 °F (110 °C)  
- Black, matte finish
- Tapped insert  
Brass, molded-in
- Threaded stud  
Steel  
- Zinc plated  
- Molded-in
- RoHS compliant

**Information**

GB1 wing nuts and GP1 wing screws offer an extended hub for better surface contact and a comfortable grip for quick two finger clamping applications.

How to order (Brass tapped insert) 1 2 <b>GB1-30-M6</b>	1	Handle diameter d <sub>1</sub>
	2	Thread d <sub>2</sub>
How to order (Steel threaded stud) 1 2 3 <b>GP1-30-M8-15</b>	1	Handle diameter d <sub>1</sub>
	2	Thread d <sub>2</sub>
	3	Length l