

NEW

Heat Shrink Tubing

Standard Polyolefin Tubings

Hoffman Heat Shrink Tubing is designed to protect inline components, splices and disconnects. Used for jacketing, wire bundles, light duty harnesses, and identifying or color coding wire, cables, and terminal components.

Material: Polyolefin

Colors: Black, Red, Blue, Yellow, White, Green, Clear

Shrink Ratio: 2:1

Operating Temperature: -55C to +125C

Minimum Shrink Temperature: 70°C

Certifications: UL224 125 C 600VC VW1, CSA C22.2 NO 198.1 OFT: RoHS Compliant

Voltage: 600V

HOFFMAN PART NO.	INSIDE DIAMETER				NOMINAL RECOVERED WALL THICKNESS AFTER HEAT		REEL QUANTITY	4 FOOT PKG QTY	6 INCH PKG QTY
	MINIMUM EXPANDED AS SUPPLIED		MAXIMUM RECOVERED AFTER HEAT		MM	IN			
	MM	IN	MM	IN					
HSTB1/16	1.50	0.059	0.65	0.026	0.35	0.014	100	25	36
HSTB1/8	3.00	0.118	1.50	0.059	0.40	0.016	100	25	28
HSTB3/16	4.50	0.177	2.30	0.091	0.50	0.020	100	25	24
HSTB1/4	6.00	0.230	3.00	0.118	0.55	0.022	100	25	20
HSTB3/8	9.00	0.354	4.50	0.177	0.60	0.024	100	25	16
HSTB1/2	12.00	0.472	6.00	0.236	0.60	0.024	100	5	14
HSTB3/4	18.00	0.709	9.00	0.354	0.80	0.031	50	5	12
HSTB1	25.00	0.984	12.50	0.492	0.90	0.035	50	5	8
HSTB1.5	40.00	1.575	20.00	0.787	1.00	0.039	50	5	5

