



MOLD TYPE	MOLD NO.	ITEM
CONN1 OVERMOLD	SRO0847	5,6
CONN1 OVERMOLD	SRO0848	4

REV.	ECN NO.	DATE	BY	DESCRIPTION
01		Sep/03/2020	Aine Li	RELEASED



AWG	CONN 1		COLOR	CONN 2
26	1	○ ○ ○ ○	BLUE	1
	2	○ ○ ○ ○	WHITE	2
	4	○ ○ ○ ○	ORANGE	4
	5	○ ○ ○ ○	WHITE	5
	6	○ ○ ○ ○	WHITE	6
	7	○ ○ ○ ○	GREEN	7
	9	○ ○ ○ ○	WHITE	9
	10	○ ○ ○ ○	BROWN	10
	SHELL		SHIELD	SHELL

ITEM	QTY	DESCRIPTION
6.	A/R	PLASTIC MASTERBATCH, BLACK, FOR TPU (A88270010001SD)
5.	A/R	TPU, SHORE A 78, NATURAL, POLYETHER, UL94V-0, HF (A51100057001SD)
4.	A/R	TPU, 94A, BLACK, UL94V-0 (A51100051001SD)
3.	2	COPPER FOIL, (W)5*(L)30mm (A4060020200SD)
2.	2	CONN., 10P, BLACK, HRS: IX40G-A-10S-CV(7.0) (A20151893001S)
1.	A/R	CABLE, ULCM, #26*4P+AM+B, BLACK, OD=6.0, CAT 6A (JPCW2421)

NOTES:

- TESTING SPEC.:
COND. RESISTANCE: 3Ω MAX.
INSUL. RESISTANCE: 10MΩ MIN.
TESTING VOLTAGE: 200V DC
- FOLLOW IPC620 CLASS II STANDARD TO ASSEMBLY AND INSPECTION.
- RoHS COMPLIANCE.

THIS DRAWING CONTAINS CONFIDENTIAL INFORMATION AND IS THE PROPERTY OF SINBON ELECTRONICS CO., LTD. IT MAY NOT BE USED OR ITS CONTENTS COPIED OR DISCLOSED TO A THIRD PARTY WITHOUT PRIOR WRITTEN CONSENT AND IS TO BE RETURNED PROMPTLY UPON REQUEST BY SINBON ELECTRONICS CO., LTD.

CUSTOMER : DigiKey		REV. : N/A	
CUSTOMER P/N : N/A		DESCRIPTION : IX(M) to IX(M), Cat6A, 500mm	
UNLESS OTHERWISE SPECIFIED TOLERANCE :		PART NUMBER : IX40AM-IX40AM-CAT6A05	
1 ~ 10 : ±1	11 ~ 30 : ±2	31 ~ 50 : ±3	51 ~ 200 : ±5
201 ~ 400 : ±7	> 401 : ±10	ANGLES : ±1°	
DRA. : Aine Li CHK. : Kevin Qiu APR. : Kevin Qiu		REV. : N/A	REV. : 01
SIZE : A3	UNIT : mm	SCALE : NONE	SHEET : 1 of 1