



## SFP+ 10GBASE-ZR/ZW, 1550nm SMF 80km Transceiver

### Features

- Maximum link length of 80km
- Hot-pluggable SFP+ footprint
- Supports 9.5 to 10.3Gb/s bit rates
- Power dissipation < 2.4W
- Single 3.3V power supply
- 1550nm EML transmitter
- Duplex LC connector
- Power dissipation < 2.4W
- Built-in digital diagnostic functions
- Case temperature range : -5°C to 70°C



### Applications

- 10GBASE-ZR/ZW 10G Ethernet

### Compliances

- Compliant with SFF-8472 SFP+ MSA.
- Compliant to SFP+ SFF-8431 and SFF-8432.
- Compliant to 802.3ae 10GBASE-ZR.
- RoHS Compliant6



## Description

The transceiver is designed for use in 10-Gigabit Ethernet APD PIN and Preamplifier in a high-integrated optical sub-assembly. Digital diagnostics functions are available via a 2-wire serial interface, as specified in SFF8472. The module data link up to 80km in 9/125um single mode fiber.

## Environmental Specifications

Parameter	Min.	Typ.	Max.	Unit
Operation Temperature	-5		+70	°C
Storage Temperature	-40	-----	+85	°C
Operation Humidity*	5	-----	85	%
Storage Humidity	5	-----	85	%

(\*) not condensing

## Operating Specifications

Parameter	Min.	Typ.	Max.	Unit
Supply Voltage	3.14	+3.3	+3.46	V
Power Dissipation			2.4	W
Transmission Distance			80	Km



## Optical Specifications

Transmitter:

Parameter	Min.	Typ.	Max.	Unit
Wavelength	1530	1550	1565	nm
Average Launch Power (each lane)	0		5	dBm
Extinction Ratio (ER)	6			dB
Spectrum Band Width (RMS)			1	Nm
SMSR	30			dB
Transmitter OFF Output Power			-40	dBm
Optical Rise/Fall Time		100	260	Ps
Transmitter and Dispersion Penalty			3	dB
Output Eye Mask	Compliant with IEEE 0802.3ae			

Receiver:

Parameter	Min.	Typ.	Max.	Unit
Input Wavelength	1270		1610	nm
Receiver Sensitivity			-23	dBm
Input Saturation Power (Overload)	-7			Psat
LOSA	-36			dBm
LOSD			-24	dBm
Hysteresis	0.5			dB

## Ordering information

Jabil Part Number	Package	Rate	Reach	Other info
JPSP10ZRLCC000L15	SFP+	10G	80 Km	DDM/RoHS

## Contact information

For additional information and evaluation samples order, please contact:

Chuck Sinha, Sr. Director of Sales

Jabil Photonics

5960 Inglewood Dr. Suite 100, Pleasanton, CA

Mobile: 408-505-0955

Email: [Chuck\\_Sinha@Jabil.com](mailto:Chuck_Sinha@Jabil.com)