



WIRING DIAGRAM

P1 P2  
 TIP INSIDE WIRE TIP  
 SHEEL BRAID SHEEL

TABLE:  
 UNLESS OTHERWISE NOTED, TOLERANCE AS FOLLOWS:

INCH	TOL.	DIMENSIONS	TOL.
.XX	±.005	X.XX	±0.13
.XXX	±.001	X.XXX	±0.25

- NOTES:
- (P1, P2) LOCKING DC POWER PLUG, MALE 2.1mm I.D. 5.5mm O.D. PLUG TYPE DC16A, COLOR BLACK PLUG IS MOLDED PER STANDARD TOOLING.
  - (C1) COAXIAL CABLE 22 AWG CABLE, VW-ISC 80°C 300V, PVC JACKET, COLOR BLACK CABLE O.D. TO BE 2.79 (1.10)
  - ALL DIMS IN PARENTHESIS ARE IN INCH.



PROJECTION

Research Development Innovation  
 RDI, Inc. 400 Columbus Avenue Valhalla, NY 10595

SCALE	NONE	TITLE	CABLE-ROHS COMPLIANT	
TOLERANCE EXCEPT AS NOTED	DR. JDEY	DATE	1/8/03	REF. LZSB-2-SLP-NL
DEC. INCHES	CK. SL	PRE-DRAWING NO.	CB-1032	SIZE A
SEE TABLE	ANG. ±1°	SEE TABLE	REV. B	

05-614	12/02/05	B	CHANGED THE PART TO ROHS COMPLIANT	MS	JY
03-687	9/25/03	A	REV'D DIMS: 48.70 WAS 47.7, 32.80 WAS 33.2	BM	SL
ECN#	DATE	SYM	REVISION RECORD	AUTH	BY

THIS DOCUMENT IS OWNED BY AND THE INFORMATION CONTAINED IN IT IS PROPRIETARY TO RDI. BY RECEIPT HEREOF THE HOLDER AGREES NOT TO USE THE INFORMATION AND NOT TO DISCLOSE IT TO ANY THIRD PARTY, NOR REPRODUCE THIS DOCUMENT WITHOUT THE WRITTEN CONSENT OF RDI, AND AGREES TO RETURN THIS DOCUMENT UPON REQUEST.