

ZBF 4,QR:FORTL.ZAHLEN 71-80 - Zack marker strip




0808820:0071

<https://www.phoenixcontact.com/us/products/0808820:0071>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

Zack marker strip flat, 10-section, horizontally labeled with the consecutive numbers: 71 ... 80, white, for terminal block width: 4 mm, mounting type: snapped



Commercial data

| | |
|--------------------------------------|---------------|
| Item number | 0808820:0071 |
| Packing unit | 1 pc |
| Minimum order quantity | 10 pc |
| Sales key | BG05 |
| Product key | BG2122 |
| GTIN | 4017918598730 |
| Weight per piece (including packing) | 0.46 g |
| Weight per piece (excluding packing) | 0.26 g |
| Customs tariff number | 49119900 |
| Country of origin | DE |

ZBF 4,QR:FORTL.ZAHLEN 71-80 - Zack marker strip



0808820:0071

<https://www.phoenixcontact.com/us/products/0808820:0071>

Technical data

Product properties

| | |
|--------------|-------------------------|
| Product type | Labeled terminal marker |
| Pitch | 4 mm |
| Type | flat |

Marking

| | |
|----------|-----------|
| Printing | 71 ... 80 |
|----------|-----------|

Mounting

| | |
|---------------|---------|
| Mounting type | snapped |
|---------------|---------|

Material specifications

| | |
|----------------------------------------|--------------------------------|
| Color | white |
| Material | PA |
| Flammability rating according to UL 94 | V2 |
| Components | free from silicone and halogen |

Environmental and real-life conditions

UV resistance

| | |
|---------------|--------------------------------|
| Specification | ISO 4892-2:2013-03 (following) |
|---------------|--------------------------------|

Ambient conditions

| | |
|-----------------------------------------------------|-------------------|
| Ambient temperature (operation) | -40 °C ... 100 °C |
| Recommended ambient temperature (storage/transport) | 23 °C |
| Recommended humidity (storage/transport) | 50 % |

Dimensions

| | |
|-------|------|
| Pitch | 4 mm |
|-------|------|

Standards and regulations

| | |
|-----------------|-----------------------------|
| Wipe resistance | DIN EN 61010-1 (VDE 0411-1) |
|-----------------|-----------------------------|

ZBF 4,QR:FORTL.ZAHLEN 71-80 - Zack marker strip



0808820:0071

<https://www.phoenixcontact.com/us/products/0808820:0071>

Classifications

ECLASS

| | |
|-------------|----------|
| ECLASS-11.0 | 27281101 |
| ECLASS-12.0 | 27281101 |
| ECLASS-13.0 | 27281101 |

ETIM

| | |
|----------|----------|
| ETIM 8.0 | EC000761 |
|----------|----------|

UNSPSC

| | |
|-------------|----------|
| UNSPSC 21.0 | 39131500 |
|-------------|----------|

Phoenix Contact 2023 © - all rights reserved

<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com