

US-EMLP (49X15) SR - Plastic label



0828902

<https://www.phoenixcontact.com/us/products/0828902>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

Plastic label, Card, silver, unlabeled, can be labeled with: BLUEMARK ID COLOR, BLUEMARK ID, THERMOMARK PRIME, THERMOMARK CARD 2.0, THERMOMARK CARD, mounting type: adhesive, lettering field size: 49 x 15 mm, Number of individual labels: 18



Your advantages

- PVC material flammability rating V0 in accordance with UL 94

Commercial data

Item number	0828902
Packing unit	1 pc
Minimum order quantity	10 pc
Sales key	BG09
Product key	BG2419
Catalog page	Page 315 (C-3-2019)
GTIN	4046356559096
Weight per piece (including packing)	18.39 g
Weight per piece (excluding packing)	17.802 g
Customs tariff number	39199080
Country of origin	DE

US-EMLP (49X15) SR - Plastic label



0828902

<https://www.phoenixcontact.com/us/products/0828902>

Technical data

Product properties

Product type	Device marking
Marking	
Number of individual labels	18
Number of individual labels per row	2

Mounting

Mounting type	adhesive
---------------	----------

Material specifications

RoHS compliant	yes
Foil strength	500 µm
Adhesive strength	50 µm
Adhesive	Acrylic
Color	silver
Material	PVC
Components	Silicone-free

Environmental and real-life conditions

Test for substances that would hinder coating with paint or varnish

Result	Test passed
--------	-------------

UV resistance

Specification	ISO 4892-2:2013-03 (following)
Result	Test passed
Test duration	96 h

Wipe resistance of inscriptions

Specification	DIN EN 61010-1 (VDE 0411-1):2011-07
	DIN EN 62208 (VDE 0660-511):2012-06 (in parts)

Testing in a condensation changing climate in the presence of sulfur dioxide

Specification	DIN 50018:2013-05
Result	Test passed
Climate level	AHT 1.0 S
Cycles	2

Salt spray test

Specification	DIN EN 60068-2-11:2000-02
Result	Test passed

Ambient conditions

Ambient temperature (operation)	-30 °C ... 80 °C
---------------------------------	------------------

US-EMLP (49X15) SR - Plastic label



0828902

<https://www.phoenixcontact.com/us/products/0828902>

Ambient temperature (storage/transport)	10 °C ... 30 °C
Permissible humidity (storage/transport)	40 % ... 70 %
Recommended storage conditions	23 °C/50 % relative humidity. Storage in a dry and dark place in the original packaging is recommended.
Recommended ambient temperature (storage/transport)	23 °C
Recommended humidity (storage/transport)	50 %
Shelf life	12 months

Dimensions

Width	48.7 mm
Height	0.5 mm
Length	14.9 mm

Standards and regulations

Wipe resistance	DIN EN 61010-1 (VDE 0411-1)
-----------------	-----------------------------

US-EMLP (49X15) SR - Plastic label



0828902

<https://www.phoenixcontact.com/us/products/0828902>

Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/0828902>



CSA

Approval ID: 70191766

US-EMLP (49X15) SR - Plastic label



0828902

<https://www.phoenixcontact.com/us/products/0828902>

Classifications

ECLASS

ECLASS-11.0	27281103
ECLASS-12.0	27281103
ECLASS-13.0	27281103

ETIM

ETIM 8.0	EC001288
----------	----------

UNSPSC

UNSPSC 21.0	39131500
-------------	----------

Phoenix Contact 2023 © - all rights reserved

<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com