




File: E209153



ISO9001:2008 Certified

**Mechanical Specifications (mm)**

D:	31.0	± max
T:	10.0	± max
Lead Diameter	1.0	± nom
S:	7.8	± nom
L:	38.0	± nom
Coating Lead Run Down (straight Leads)	4.0	± max
B:	7.80	± nom
C:	6.70	± nom



**Electrical Specifications**

Resistance:	20.0 Ω	± 25 %
Max Steady State Current upto 65°C:	10.00	A
Max Rec. Energy Rating:	250	J
Actual Failure Instantaneous Energy:	500	J
Maximum Capacitance @ 120 VAC:	17,000	µf
Maximum Capacitance @ 240 VAC:	4,341	µf
Maximum Capacitance @ 440 VAC:	1,003	µf
Maximum Capacitance @ 680 VAC:	500	µf
Resistance @ 100% Max Current:	0.00	Ω
Resistance @ 50% Max Current:	0.64	Ω
Body Temperature at 100% Max Current:	224.00	°c
Dissipation Constant:	45.4	mw/°c
Thermal Time Constant:	194	Sec.
Material Type (for Beta and Curve):	I	

<b>MS32 20010</b>	
Date: 02/05/2009	Drawn by: Erin Landis
Ametherm, Inc. 961 Fairview Drive Carson City, Nevada USA 89701 www.ametherm.com	Approved By: Mehdi Samii
	Revision: A