


# PABA YE/15 - Insert label

1013698

<https://www.phoenixcontact.com/us/products/1013698>



Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Insert label, Strip, yellow, unlabeled, can be labeled with: CMS-P1-PLOTTER, mounting type: slide-on, cable diameter range: 0.6 ... 50 mm, lettering field size: 15 x 4 mm, Number of individual labels: 20

## Commercial data

Item number	1013698
Packing unit	1 pc
Minimum order quantity	50 pc
Sales key	BG20
Product key	BG2213
Catalog page	Page 421 (CL-2005)
GTIN	4017918013882
Weight per piece (including packing)	6.15 g
Weight per piece (excluding packing)	4.2 g
Customs tariff number	39269097
Country of origin	CN

## Technical data

### Notes

General	Can be labeled with CMS
---------	-------------------------


### Product properties

Product type	Conductor marking
--------------	-------------------

### Marking

Number of individual labels	20
Number of individual labels per row	1

### Dimensions

Dimensional drawing	
Width	15 mm
Length	4 mm

### Material specifications

Color	yellow
Material	ABS
Flammability rating according to UL 94	V0

### Cable/line

External cable diameter	0.6 mm ... 50 mm
-------------------------	------------------

### Environmental and real-life conditions

#### Test for substances that would hinder coating with paint or varnish

Result	Test passed
--------	-------------

#### Scratch test for the determining scratch resistance

Specification	DIN EN ISO 1518-1:2019-10 (following)
Requirements	≥ 5 N
Result	Test passed

#### Tesa film test

Specification	DIN EN ISO 2409:2013 (following)
Result	Test passed

#### UV resistance

Specification	ISO 4892-2:2013-03 (following)
Result	Test passed

# PABA YE/15 - Insert label



1013698

<https://www.phoenixcontact.com/us/products/1013698>

Test duration	96 h
---------------	------

## Temperature resistance

Specification	ANSI/UL 969-2018:03 (following)
Test duration	240 h
Rating 80 °C (105 °C)	Test passed
Specification	ISO 175:2010 (following)
Test duration	168 h

## Testing in a condensation changing climate in the presence of sulfur dioxide

Specification	DIN 50018:2013-05
Result	Test passed
Climate level	AHT 1.0 S
Cycles	2

## Salt spray test

Specification	DIN EN 60068-2-11:2000-02
Result	Test passed
Test duration	96 h

## Ambient conditions

Ambient temperature (operation)	-15 °C ... 65 °C
Recommended ambient temperature (storage/transport)	23 °C
Recommended humidity (storage/transport)	50 % (Storage in a dry and dark place in the original packaging is recommended)

## Standards and regulations

Wipe resistance	DIN EN 61010-1 (VDE 0411-1)
-----------------	-----------------------------

## Mounting

Mounting type	slide-on
---------------	----------

# PABA YE/15 - Insert label

1013698

<https://www.phoenixcontact.com/us/products/1013698>



## Classifications

### ECLASS

ECLASS-11.0	27281102
ECLASS-12.0	27281102
ECLASS-13.0	27281102

### ETIM

ETIM 8.0	EC001530
----------	----------

### UNSPSC

UNSPSC 21.0	39131500
-------------	----------

Phoenix Contact 2023 © - all rights reserved

<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)