

1019678
<https://www.phoenixcontact.com/us/products/1019678>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Crimp splice protection, design: Straight, degree of protection: IP20, connection method: Crimp connection, cable outlet: above and below, color: Bare metallic

Product description

Crimp splice protection in blister packaging

Your advantages

- No attenuating effects on the fusion splice
- Mechanical protection for fusion splices
- Telekom TS 0338/96 approval

Commercial data

| | |
|--------------------------------------|---------------------|
| Item number | 1019678 |
| Packing unit | 1 pc |
| Minimum order quantity | 12 pc |
| Sales key | AB15 |
| Product key | ABNGAZ |
| Catalog page | Page 381 (C-2-2019) |
| GTIN | 4055626701189 |
| Weight per piece (including packing) | 0.53 g |
| Weight per piece (excluding packing) | 0.3 g |
| Customs tariff number | 85367000 |
| Country of origin | DE |

FOC-CRIMPSPLICE-PROTECT - Crimp splice protection



1019678

<https://www.phoenixcontact.com/us/products/1019678>

Technical data

Notes

| | |
|---------|------------------------------------------------|
| General | Splice protection for FDX 20 splice boxes |
| General | Processing with commercially-available presses |

Product properties

| | |
|--------------|-----------------|
| Product type | Data plug |
| Housing type | Fiber optic |
| Cable outlet | above and below |

Dimensions

| | |
|--------|--------|
| Height | 3 mm |
| Depth | 1.2 mm |
| Length | 30 mm |

Material specifications

| | |
|----------|---------------|
| Color | Bare metallic |
| Material | Metal |

Cable/line

| | |
|-----------------------------|-----------------------------------|
| Cable type | Fiberglass |
| External cable diameter () | 250 µm (Includes primary coating) |

FO cable

| | |
|---------------------|----|
| Transmission medium | FO |
|---------------------|----|

Environmental and real-life conditions

Ambient conditions

| | |
|---------------------------------|------------------------------------------------|
| Degree of protection | IP20 |
| | IP20 |
| Ambient temperature (operation) | -40 °C ... 85 °C (according to DIN EN 61300-2) |

Mounting

| | |
|-----------------------|-------------------------------------------------------|
| Mounting type | Crimp splice protection |
| Assembly instructions | Crimp splice protection clicks into the splice holder |
| Connection method | Crimp connection |

FOC-CRIMPSPLICE-PROTECT - Crimp splice protection



1019678

<https://www.phoenixcontact.com/us/products/1019678>

Classifications

ECLASS

| | |
|-------------|----------|
| ECLASS-11.0 | 27144492 |
| ECLASS-12.0 | 27144492 |
| ECLASS-13.0 | 27144492 |

ETIM

| | |
|----------|----------|
| ETIM 8.0 | EC002609 |
|----------|----------|

UNSPSC

| | |
|-------------|----------|
| UNSPSC 21.0 | 26121650 |
|-------------|----------|

FOC-CRIMPSPLICE-PROTECT - Crimp splice protection



1019678
<https://www.phoenixcontact.com/us/products/1019678>

Environmental product compliance

| | |
|------------|---------------------------------------------------------|
| China RoHS | Environmentally friendly use period: unlimited = EFUP-e |
| | No hazardous substances above threshold values |

Phoenix Contact 2023 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com