

FBP-3F/14 4U AUX - Blind plug

1029339

<https://www.phoenixcontact.com/us/products/1029339>



Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Blind plug, nom. voltage: 250 V, nominal current: 24 A, number of positions: 14, Rated cross section: 6 mm², color: gray

Commercial data

| | |
|--------------------------------------|---------------------|
| Item number | 1029339 |
| Packing unit | 1 pc |
| Minimum order quantity | 1 pc |
| Sales key | BE06 |
| Product key | BE6114 |
| Catalog page | Page 651 (C-1-2019) |
| GTIN | 4055626531397 |
| Weight per piece (including packing) | 164 g |
| Weight per piece (excluding packing) | 164 g |
| Customs tariff number | 85389099 |
| Country of origin | PL |

FBP-3F/14 4U AUX - Blind plug

1029339

<https://www.phoenixcontact.com/us/products/1029339>



Technical data

Product properties

| | |
|---------------------|------------|
| Product type | Blind plug |
| Number of positions | 14 |

Connection data

| | |
|-----------------------|-------------------|
| Nominal current | 24 A |
| Maximum load current | 24 A |
| Nominal voltage | 250 V |
| Nominal cross section | 6 mm ² |

Material specifications

| | |
|--|------|
| Color | gray |
| Flammability rating according to UL 94 | V0 |
| Insulating material | PC |

Environmental and real-life conditions

Ambient conditions

| | |
|--|---|
| Ambient temperature (storage/transport) | -25 °C ... 55 °C (for a short time, not exceeding 24 h, -60 °C to +70 °C) |
| Ambient temperature (assembly) | -5 °C ... 70 °C |
| Ambient temperature (actuation) | -5 °C ... 70 °C |
| Permissible humidity (storage/transport) | 30 % ... 70 % |

FBP-3F/14 4U AUX - Blind plug

1029339

<https://www.phoenixcontact.com/us/products/1029339>



Drawings

Circuit diagram



FBP-3F/14 4U AUX - Blind plug

1029339

<https://www.phoenixcontact.com/us/products/1029339>



Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/1029339>



CSA

Approval ID: 13631



cUL Recognized

Approval ID: FILE E 60425



UL Recognized

Approval ID: FILE E 60425

cULus Recognized

FBP-3F/14 4U AUX - Blind plug

1029339

<https://www.phoenixcontact.com/us/products/1029339>



Classifications

ECLASS

| | |
|-------------|----------|
| ECLASS-11.0 | 27141190 |
| ECLASS-13.0 | 27141190 |
| ECLASS-12.0 | 27141190 |

ETIM

| | |
|----------|----------|
| ETIM 8.0 | EC002848 |
|----------|----------|

UNSPSC

| | |
|-------------|----------|
| UNSPSC 21.0 | 39121400 |
|-------------|----------|

FBP-3F/14 4U AUX - Blind plug

1029339

<https://www.phoenixcontact.com/us/products/1029339>



Environmental product compliance

| | |
|------------|--|
| REACH SVHC | Lead 7439-92-1 |
| China RoHS | Environmentally Friendly Use Period = 50 years |
| | For information on hazardous substances, refer to the manufacturer's declaration available under "Downloads" |

FBP-3F/14 4U AUX - Blind plug

1029339

<https://www.phoenixcontact.com/us/products/1029339>




Accessories

BTFE 6-3/14 4U AUX - Test terminal strip

1029025

<https://www.phoenixcontact.com/us/products/1029025>



Test terminal strip, nom. voltage: 400 V, nominal current: 24 A, number of positions: 14, connection method: Ring cable lug, 1 level, mounting type: 19" rack mounting, color: gray

TMT (EX6,2)R - Marker for terminal blocks

0803063

<https://www.phoenixcontact.com/us/products/0803063>



Marker for terminal blocks, Roll, white, unlabeled, can be labeled with: THERMOMARK E.300 (D)/600 (D), THERMOMARK ROLL 2.0, THERMOMARK ROLL, THERMOMARK ROLL X1, THERMOMARK ROLLMASTER 300/600, THERMOMARK X1.2, mounting type: snapped, snap into flat marker groove, lettering field size: 6.2 x 50000 mm, Number of individual labels: 1

FBP-3F/14 4U AUX - Blind plug

1029339

<https://www.phoenixcontact.com/us/products/1029339>



US-TMF 100 - Marker for terminal blocks

0829260

<https://www.phoenixcontact.com/us/products/0829260>



Marker for terminal blocks, Card, white, unlabeled, can be labeled with: BLUEMARK ID COLOR, BLUEMARK ID, THERMOMARK PRIME, THERMOMARK CARD 2.0, THERMOMARK CARD, mounting type: snapped, snap into flat marker groove, lettering field size: 104 x 6.6 mm, Number of individual labels: 20

ZBF 8:UNBEDRUCKT - Zack Marker strip, flat

0808781

<https://www.phoenixcontact.com/us/products/0808781>



Zack Marker strip, flat, Strip, white, unlabeled, can be labeled with: PLOTMARK, CMS-P1-PLOTTER, mounting type: snapped, for terminal block width: 8 mm, lettering field size: 5.15 x 8.15 mm, Number of individual labels: 10

FBP-3F/14 4U AUX - Blind plug

1029339

<https://www.phoenixcontact.com/us/products/1029339>



ZBF 8 CUS - Zack Marker strip, flat

0825030

<https://www.phoenixcontact.com/us/products/0825030>



Zack Marker strip, flat, can be ordered: Strip, white, labeled according to customer specifications, mounting type: snap into flat marker groove, for terminal block width: 8 mm, lettering field size: 5.15 x 8.15 mm, Number of individual labels: 10

ZBF 8,LGS:FORTL.ZAHLEN - Zack Marker strip, flat

0808804

<https://www.phoenixcontact.com/us/products/0808804>



Zack Marker strip, flat, Strip, white, labeled, printed horizontally: consecutive numbers 1 ... 10, 11 ... 20, etc. up to 101 ... 110, mounting type: snapped, for terminal block width: 8 mm, lettering field size: 5.15 x 8.15 mm, Number of individual labels: 10

FBP-3F/14 4U AUX - Blind plug

1029339

<https://www.phoenixcontact.com/us/products/1029339>



UC-TMF 8 - Marker for terminal blocks

0818137

<https://www.phoenixcontact.com/us/products/0818137>



Marker for terminal blocks, Sheet, white, unlabeled, can be labeled with: BLUEMARK ID COLOR, BLUEMARK ID, BLUEMARK CLED, PLOTMARK, CMS-P1-PLOTTER, mounting type: snapped, for terminal block width: 8.2 mm, lettering field size: 7.6 x 5.1 mm, Number of individual labels: 56

UC-TMF 8 CUS - Marker for terminal blocks

0824654

<https://www.phoenixcontact.com/us/products/0824654>



Marker for terminal blocks, can be ordered: by sheet, white, labeled according to customer specifications, mounting type: snap into flat marker groove, for terminal block width: 8.2 mm, lettering field size: 7.6 x 5.1 mm, Number of individual labels: 56

FBP-3F/14 4U AUX - Blind plug

1029339

<https://www.phoenixcontact.com/us/products/1029339>



UCT-TMF 8 - Marker for terminal blocks

0828748

<https://www.phoenixcontact.com/us/products/0828748>



Marker for terminal blocks, Sheet, white, unlabeled, can be labeled with: TOPMARK NEO, TOPMARK LASER, BLUEMARK ID COLOR, BLUEMARK ID, BLUEMARK CLED, THERMOMARK PRIME, THERMOMARK CARD 2.0, THERMOMARK CARD, mounting type: snapped, for terminal block width: 8.2 mm, lettering field size: 7.4 x 4.7 mm, Number of individual labels: 42

UCT-TMF 8 CUS - Marker for terminal blocks

0829672

<https://www.phoenixcontact.com/us/products/0829672>



Marker for terminal blocks, can be ordered: by sheet, white, labeled according to customer specifications, mounting type: snap into flat marker groove, for terminal block width: 8.2 mm, lettering field size: 7.4 x 4.7 mm, Number of individual labels: 42

Phoenix Contact 2023 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com