

# PV-ED6/Y-120(1+/2-) - Photovoltaic Y-distributor



1030650

<https://www.phoenixcontact.com/us/products/1030650>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

Photovoltaic Y-distributor, Range of articles: Sunclix, housing material: PPE, color: black



## Your advantages

- Suitable for current and future requirements with nominal voltages up to 1500 V
- Easy installation provides increased safety and time savings
- Easy integration into existing systems with preassembled modules
- Different numbers of node outlets and customer-specific cable lengths available on request

## Commercial data

Item number	1030650
Packing unit	1 pc
Minimum order quantity	10 pc
Sales key	AB02
Product key	ABLBCA
GTIN	4055626533483
Weight per piece (including packing)	112.9 g
Weight per piece (excluding packing)	112.9 g
Customs tariff number	85446010
Country of origin	DE

## Technical data

### Notes

#### Safety note

##### Safety note

- **WARNING:** Commission properly functioning products only. The products must be regularly inspected for damage. Decommission defective products immediately. Replace damaged products. Repairs are not possible.
- **WARNING:** Only electrically qualified personnel may install and operate the product. They must observe the following safety notes. The qualified personnel must be familiar with the basics of electrical engineering. They must be able to recognize and prevent danger. The relevant symbol on the packaging indicates that only personnel familiar with electrical engineering are allowed to install and operate the product.
- **WARNING:** The connectors may not be plugged in or disconnected under load. Ignoring the warning or improper use may damage persons and/or property.
- The products are suitable for applications in plant, controller, and electrical device engineering.
- Assembled products may not be manipulated or improperly opened.
- Only use mating connectors that are specified in the technical data of the standards listed (e.g. the ones listed in the product accessories online at [phoenixcontact.com/products](https://www.phoenixcontact.com/products)).
- When using the product in direct connection with third-party manufacturers, the user is responsible.
- For operating voltages > 50 V AC, conductive connector housings must be grounded
- Ensure that the protective or functional ground has been properly connected.
- Observe the corresponding technical data. You will find information:
  - o On the product
  - o On the packing label
  - o In the supplied documentation
  - o Online at [phoenixcontact.com/products](https://www.phoenixcontact.com/products) under the product
- The installation notes/Design In documents online on the download page at [phoenixcontact.com/products](https://www.phoenixcontact.com/products) must be observed for this product.
- Use a protective cap to protect connectors that are not in use. The suitable accessories are available online in the accessory section of the product at [phoenixcontact.com/products](https://www.phoenixcontact.com/products)
- The connector warms up in normal operation. Depending on the ambient conditions, the surface of the connector can continue to warm up. In this case, the user is responsible for posting warnings (e.g. DIN EN ISO 13732-1:2008-12).
- Operate the connector only when it is fully plugged in and interlocked.
- Ensure that when laying the cable, the tensile load on the connectors does not exceed the upper limit specified in the standards.

# PV-ED6/Y-120(1+1/2-) - Photovoltaic Y-distributor



1030650

<https://www.phoenixcontact.com/us/products/1030650>

- Observe the minimum bending radius of the cable. Lay the cable without twisting it.

## Product properties

Product type	Power distributor
Product family	Sunclix

## Insulation characteristics

Degree of pollution	2
---------------------	---

## Dimensions

Length	120 mm
--------	--------

## Electrical properties

Rated voltage (II/2)	1000 V
Rated voltage (III/2)	1500 V
Rated surge voltage (II/2)	12 kV
Rated surge voltage (III/2)	12 kV
Rated surge voltage (III/3)	16 kV

## Material specifications

Color	black
Color of the housing part	black
Flammability rating according to UL 94	V0
Insulating material group	I / CTI 600
Cable seal material	EPDM
Contact material	Cu
Contact surface material	Ag
Contact carrier material	PPE
O-ring material	Silopren
Housing material	PPE

## Cable/line

Cable type	H1Z2Z2-K
------------	----------

## Environmental and real-life conditions

### Ambient conditions

Ambient temperature (operation)	-40 °C ... 85 °C
---------------------------------	------------------

# PV-ED6/Y-120(1+/2-) - Photovoltaic Y-distributor



1030650

<https://www.phoenixcontact.com/us/products/1030650>

## Approvals

🔗 To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/1030650>



**EAC**

Approval ID: B.01687

# PV-ED6/Y-120(1+/2-) - Photovoltaic Y-distributor



1030650

<https://www.phoenixcontact.com/us/products/1030650>

## Classifications

### ECLASS

ECLASS-11.0	27060313
ECLASS-12.0	27060313
ECLASS-13.0	27060313

### ETIM

ETIM 8.0	EC001855
----------	----------

### UNSPSC

UNSPSC 21.0	26121600
-------------	----------

# PV-ED6/Y-120(1+/2-) - Photovoltaic Y-distributor



1030650  
<https://www.phoenixcontact.com/us/products/1030650>

## Environmental product compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Phoenix Contact 2023 © - all rights reserved  
<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)