

# HS LC-H-D2C/ R2XC1-2,54 - Fiber optic



1036658

<https://www.phoenixcontact.com/us/products/1036658>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Multiple light guides with glare protection, passive, rigid, can be used for the ME, ME-MAX, ME-IO, ME PLC, and EH housing ranges (housing must be processed)

## Your advantages

- Light guides are perfectly matched to electronics housings
- Easy mounting on the PCB using press pins
- Resistance to ESD
- Housing processing available on request
- Enables simple visual status and diagnostic indicators

## Commercial data

Item number	1036658
Packing unit	1 pc
Minimum order quantity	100 pc
Sales key	AC05
Product key	ACGABA
GTIN	4055626541884
Weight per piece (including packing)	0.44 g
Weight per piece (excluding packing)	0.32 g
Customs tariff number	90019000
Country of origin	TN

# HS LC-H-D2C/ R2XC1-2,54 - Fiber optic



1036658

<https://www.phoenixcontact.com/us/products/1036658>

## Technical data

### Notes

General	Refer to the data sheet for the range in the download area.
General	The tops of the press-in pegs are conical to make installation easier.
General	To prevent glare, the system has an aperture. This also makes mixed colors possible.

### Product properties

Product type	Fiber optic
Number of positions	2
Pitch	2.54 mm
Number of rows	2
Alignment	Horizontal
Type	passive, rigid
Conductor type	Multiple light guides with glare protection
Head form	Raised head, conical
Number of indicators	2 (2 rows x 1 column)

### Electrical properties

ESD protection	< 8 kV
----------------	--------

### Dimensions

Diameter	2 mm
Hole diameter	1.2 mm
Pitch	2.54 mm

### Material specifications

Color Lichtleiter	transparent
Color Blende	black (9005)
Color (Light guide)	transparent
Flammability rating according to UL 94	HB
Insulating material	Polycarbonat

### Environmental and real-life conditions

#### Ambient conditions

Max. IP code to attain	IP20
Ambient temperature (operation)	-40 °C ... 85 °C

# HS LC-H-D2C/ R2XC1-2,54 - Fiber optic



1036658

<https://www.phoenixcontact.com/us/products/1036658>

## Classifications

### ECLASS

ECLASS-11.0	27182702
ECLASS-13.0	27460404

### ETIM

ETIM 8.0	EC001031
----------	----------

### UNSPSC

UNSPSC 21.0	31261500
-------------	----------

# HS LC-H-D2C/ R2XC1-2,54 - Fiber optic



1036658

<https://www.phoenixcontact.com/us/products/1036658>

## Environmental product compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Phoenix Contact 2023 © - all rights reserved  
<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)