

BL2 BPC 1501S-W - Box PC



1141904

<https://www.phoenixcontact.com/us/products/1141904>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



IP30-rated fanless industrial box PC (BPC) with energy-efficient Intel® Celeron® N3350 processor, 32 GB eMMC mass storage, and Wi-Fi

Commercial data

Item number	1141904
Packing unit	1 pc
Sales key	DR12
Product key	DRBABA
GTIN	4063151101800
Weight per piece (including packing)	774 g
Weight per piece (excluding packing)	614 g
Country of origin	TW

BL2 BPC 1501S-W - Box PC

1141904

<https://www.phoenixcontact.com/us/products/1141904>



Technical data

Product properties

Product type	Box PC
--------------	--------

Computer data

Processor	Intel® Celeron® N3350 1.10/2.4 GHz
Operating system	without operating system
Cooling	passive
RAM	2 GB LPDDR4
Data storage system	eMMC internal, 32 GB

Display

Display type	none
--------------	------

System properties

User software	without user software
---------------	-----------------------

Electrical properties

Maximum power dissipation for nominal condition	16.8 W
-------------------------------------------------	--------

Supply

Supply voltage (DC)	24 V DC (CE rating)
Supply voltage range	12 V DC ... 30 V DC (Labeled operational voltage is 12 ... 30 V DC)
Max. current consumption	0.7 A (24 V DC)
Typical current consumption	0.53 A (24 V DC)

Connection data

Screw connection

Connection method	Screw connection
Conductor cross section, rigid	0.2 mm² ... 2.5 mm²
Conductor cross section, flexible	0.2 mm² ... 2.5 mm²
Conductor cross section AWG	25 ... 14

Interfaces

Interfaces	1x DP++
	2x USB 3.0
	1x Wireless LAN
Network	2x Ethernet (10/100/1000 Mbps), RJ45
LAN chipset	Intel® I210-AT

Dimensions

External dimensions

Width / Height / Depth	99 mm / 92 mm / 46 mm
------------------------	-----------------------

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP30
	IP30
Ambient temperature (operation)	-20 °C ... 50 °C (with 0.5 m/s airflow)
Ambient temperature (storage/transport)	-40 °C ... 85 °C
Permissible humidity (operation)	5 % ... 85 % (non-condensing)
Shock	15g, 11 ms in accordance with IEC 60068-2-27
Vibration (operation)	1g, according to EN 60068-2-6

Approvals

Conformity/Approvals

Conformance	CE-compliant
FCC	Title 47 Part 15 Subpart B:2018 Class A

Mounting

Mounting type	DIN rail mounting
	Wall mounting (Accessories required)

BL2 BPC 1501S-W - Box PC



1141904

<https://www.phoenixcontact.com/us/products/1141904>

Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/1141904>



EAC

Approval ID: RU C-DE.A*08.B01708



UL Listed

Approval ID: FILE E 238705



cUL Listed

Approval ID: FILE E 238705

cULus Listed

BL2 BPC 1501S-W - Box PC



1141904

<https://www.phoenixcontact.com/us/products/1141904>

Classifications

ECLASS

ECLASS-11.0	19200102
ECLASS-12.0	19200102
ECLASS-13.0	19200102

ETIM

ETIM 8.0	EC001413
----------	----------

UNSPSC

UNSPSC 21.0	43211500
-------------	----------

BL2 BPC 1501S-W - Box PC



1141904

<https://www.phoenixcontact.com/us/products/1141904>

Environmental product compliance

REACH SVHC	Lead 7439-92-1
------------	----------------

Phoenix Contact 2023 © - all rights reserved

<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com