

AS-WB-F/T-BOARD A1 210X300 - Workbench foam insert



1194547

<https://www.phoenixcontact.com/us/products/1194547>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

Foam insert with machined contour for storing hand tools and accessories in accordance with the 5S principle, compatible with the AS-WORKBENCH-F ...



Commercial data

Item number	1194547
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	BH31
Product key	BH371Z
GTIN	4063151248291
Weight per piece (including packing)	175 g
Weight per piece (excluding packing)	175 g
Customs tariff number	39239000
Country of origin	DE

AS-WB-F/T-BOARD A1 210X300 - Workbench foam insert



1194547

<https://www.phoenixcontact.com/us/products/1194547>

Technical data

Notes

General	Items that can be placed directly on or in this foam insert
---------	---

Product properties

Product type	Workbench foam insert
--------------	-----------------------

Dimensions

Width	210 mm
Height	30 mm
Length	305 mm

Material specifications

Color	anthracite
-------	------------

AS-WB-F/T-BOARD A1 210X300 - Workbench foam insert



1194547

<https://www.phoenixcontact.com/us/products/1194547>

Classifications

ECLASS

ECLASS-11.0	21101046
ECLASS-12.0	21101046
ECLASS-13.0	21101046

ETIM

ETIM 8.0	EC011819
----------	----------

UNSPSC

UNSPSC 21.0	22101500
-------------	----------

AS-WB-F/T-BOARD A1 210X300 - Workbench foam insert



1194547

<https://www.phoenixcontact.com/us/products/1194547>

Accessories

UNIFOX-P VDE - Pointed pliers

1212204

<https://www.phoenixcontact.com/us/products/1212204>



Needle-nose pliers with blade, notched grip area,
VDE 1000 V AC/1500 V DC tested

CRIMPFOX DUO 10 - Crimping pliers

1031721

<https://www.phoenixcontact.com/us/products/1031721>



Crimping pliers, contact connection type: Insulated and uninsulated ferrules, standards/specifications: DIN 46228-1, DIN 46228-4, UL 486F, form A, E, F, min. cross section: 0.14 mm², max. cross section: 10 mm², for TWIN ferrules up to 2 x 4 mm², automatic cross section adjustment, rotating die, lateral and frontal insertion, compression: Trapezoidal crimp, black/green

AS-WB-F/T-BOARD A1 210X300 - Workbench foam insert



1194547

<https://www.phoenixcontact.com/us/products/1194547>

CUTFOX-MPS - Cutting tool

1139725

<https://www.phoenixcontact.com/us/products/1139725>



Multifunctional scissors, micro-serrated cutting area, suitable for cardboard, aluminum, Kevlar fibers, and plastic, outside blade edge can be used to safely cut adhesive tape, two-component non-slip soft-grip handles, ergonomic design, adjustable screw joint, with protective cover

WIREFOX 10 - Stripping tool

1212150

<https://www.phoenixcontact.com/us/products/1212150>



Stripping tool, for cables and conductors from 0.02 - 10 mm², self-adjusting, stripping length of up to 18 mm, cutting capacity of up to 10 mm² stranded/1.5 mm² solid, replaceable stripping blade

AS-WB-F/T-BOARD A1 210X300 - Workbench foam insert



1194547

<https://www.phoenixcontact.com/us/products/1194547>

SF-SL 0,8X4,0-100 S-VDE - Screwdriver

1212588

<https://www.phoenixcontact.com/us/products/1212588>



Actuation tool, for ST terminal blocks, VDE insulated, with slimmer insulation integrated in the blade, also suitable for use as a bladed screwdriver, size: 0.8 x 4.0 x 100 mm, 2-component grip, with non-slip grip

ST-BW - Actuation tool

1207608

<https://www.phoenixcontact.com/us/products/1207608>



Actuation tool, for all 2.5 mm² - 4.0 mm² spring-cages

Phoenix Contact 2023 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com