

CHARX SEC-3000 - AC charging controller



1139022

<https://www.phoenixcontact.com/us/products/1139022>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



CHARX control modular, AC charging controller, with Embedded Linux system, IEC 61851-1, operating mode: Stand-Alone, Client, Server, interface: Ethernet (2x), CHARX control modular system bus, MICRO-USB type C, communication protocol: OCPP 1.6J, Modbus/TCP, MQTT, Connectable peripheral devices: Energy meter, RFID, DC residual current detection, DIN rail mounting

Commercial data

Item number	1139022
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	EM01
Product key	XWBBFC
GTIN	4063151086510
Weight per piece (including packing)	242.5 g
Weight per piece (excluding packing)	242 g
Customs tariff number	85371091
Country of origin	DE

CHARX SEC-3000 - AC charging controller



1139022

<https://www.phoenixcontact.com/us/products/1139022>

Technical data

Product properties

Product type	AC charging controller
Product family	CHARX control modular
Design	with Embedded Linux system
Operating mode	Stand-Alone
	Client
	Server
Charging standard	IEC 61851-1
Charging mode	Mode 3, Case B + C

Insulation characteristics

Overvoltage category	III
----------------------	-----

System properties

IEC 61131 runtime system

Data storage system	8 GByte (eMMC)
---------------------	----------------

Electrical properties

Supply

Supply voltage	12 V DC $\pm 5\%$
Supply voltage range	11.4 V DC ... 12.6 V DC
Max. current consumption	2 A (Stand-alone operation)

Input data

Digital

Number of digital inputs	4
Description of the input	Digital input
Nominal input voltage U_N	12 V
Input voltage range U1	0 V ... 3 V (Off)
Input voltage range U2	9 V ... 15 V (On)

Output data

Digital

Output name	Digital output
Number outputs	4
Maximum output voltage	≤ 12 V (Low-side operation)
Maximum output current	max. 600 mA

Connection data

Conductor connection

CHARX SEC-3000 - AC charging controller



1139022

<https://www.phoenixcontact.com/us/products/1139022>

Connection method	pluggable
	Push-in technology
Conductor cross section rigid	0.14 mm² ... 1.5 mm²
Conductor cross section flexible	0.2 mm² ... 2.5 mm²
Conductor cross section AWG	24 ... 16

Interfaces

Interface	Ethernet (2x)
	CHARX control modular system bus
	USB-C

Ethernet

Interface	Ethernet
Connection method	RJ45 jack
Number of interfaces	2
Number of supported devices	2
Serial transmission speed	10/100 Mbps
Transmission length	100 m
Protocols supported	OCPP 1.6J
	Modbus/TCP
	MQTT
	HTTP
	HTTPS

Others

Interface	Configuration and diagnostics
Connection method	Micro-USB type C
Number of interfaces	1
Protocols supported	RNDIS

Others

Interface	Energy meter
Bus system	RS-485
Transmission speed range	9.6 kbps ... 115.2 kbps (Automatic setting in accordance with the selected energy meter)

Others

Interface	RFID readers
Bus system	RS-485
Transmission speed range	9.6 kbps ... 115.2 kbps (Automatic setting in accordance with the selected RFID reader)

Others

Interface	CHARX control modular system bus
Connection method	DIN rail bus connectors
Number of interfaces	1

CHARX SEC-3000 - AC charging controller



1139022

<https://www.phoenixcontact.com/us/products/1139022>

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP20
Ambient temperature (operation)	-25 °C ... 65 °C
Ambient temperature (storage/transport)	-40 °C ... 80 °C
Permissible humidity (operation)	5 % ... 95 % (non-condensing)
Permissible humidity (storage/transport)	5 % ... 95 % (non-condensing)
Air pressure (operation)	70 kPa ... 106 kPa (up to 3000 m above mean sea level)
Air pressure (storage/transport)	58 kPa ... 106 kPa (up to 4500 m above mean sea level)

Approvals

Conformity/Approvals

Conformance	CE-compliant
-------------	--------------

Standards and regulations

Standards

Standards/regulations	IEC 61851-1
-----------------------	-------------

Mounting

Mounting type	DIN rail mounting
Assembly instructions	DIN rail mounting
Mounting position	any

CHARX SEC-3000 - AC charging controller

1139022

<https://www.phoenixcontact.com/us/products/1139022>



Classifications

ECLASS

ECLASS-11.0	27144703
ECLASS-12.0	27144703
ECLASS-13.0	27144703

ETIM

ETIM 8.0	EC002889
----------	----------

UNSPSC

UNSPSC 21.0	39121800
-------------	----------

CHARX SEC-3000 - AC charging controller



1139022

<https://www.phoenixcontact.com/us/products/1139022>

Environmental product compliance

REACH SVHC	Lead 7439-92-1
China RoHS	Environmentally Friendly Use Period = 50 years
	For information on hazardous substances, refer to the manufacturer's declaration available under "Downloads"

CHARX SEC-3000 - AC charging controller



1139022

<https://www.phoenixcontact.com/us/products/1139022>

Accessories

EV-RCM-6DC-WAT - Differential current monitoring

1309697

<https://www.phoenixcontact.com/us/products/1309697>



The residual current monitoring module is used for AC and DC residual current detection in AC charging points. The higher-level safety equipment (e.g., residual current device) is protected against potential DC residual currents.

EV-RCM-6DC-WAT-X10 - Differential current monitoring

1309695

<https://www.phoenixcontact.com/us/products/1309695>



The residual current monitoring module is used for AC and DC residual current detection in AC charging points. The higher-level safety equipment (e.g., residual current device) is protected against potential DC residual currents.

CHARX SEC-3000 - AC charging controller



1139022

<https://www.phoenixcontact.com/us/products/1139022>

EV-RFID-ELT-PCB - RFID device

1309772

<https://www.phoenixcontact.com/us/products/1309772>



CHARX control, RFID device, for connection to CHARX control modular AC charging controllers

EV-RFID-ELT-PCB-X10 - RFID device

1309752

<https://www.phoenixcontact.com/us/products/1309752>



CHARX control, RFID device, for connection to CHARX control modular AC charging controllers

CHARX SEC-3000 - AC charging controller



1139022

<https://www.phoenixcontact.com/us/products/1139022>

EV-RFID-ELT-IP65 - RFID device

1309687

<https://www.phoenixcontact.com/us/products/1309687>

CHARX control, RFID device, for connection to CHARX control modular AC charging controllers, in housing



CHARX SEC JST-RCM-CBL - Cable set

1360462

<https://www.phoenixcontact.com/us/products/1360462>

CHARX control modular, Cable set, 4-pos., with plug-in contact at one end, Exclusively for connecting the EV-RCM-6DC-WAT residual current sensor, Item no.: 1309697 to modules in the CHARX control modular charging controller family, length: 0.4 m



CHARX SEC-3000 - AC charging controller

1139022


<https://www.phoenixcontact.com/us/products/1139022>



CHARX 4,3 LCD DISPLAY - Display

1426836

<https://www.phoenixcontact.com/us/products/1426836>



LCD color display, 4.3", including preinstalled charging software for electric vehicles, micro USB port, adhesive mounting (mounting material not supplied as standard), up to 12 charging points

EV-T2M3SO12-3P-P-SET - Infrastructure charging socket

1164422

<https://www.phoenixcontact.com/us/products/1164422>



CHARX connect modular, Infrastructure charging socket, square, Premium, Set, with square protective cover, with temperature sensors, with LED (common cathode connection), for charging electric vehicles (EV) with alternating current (AC), Type 2, IEC 62196-2, 32 A / 480 V (AC), without single-core wires, locking actuator: 12 V, 3-pos., Rear panel mounting, M5 thread, housing: black, PHOENIX CONTACT logo

CHARX SEC-3000 - AC charging controller



1139022

<https://www.phoenixcontact.com/us/products/1139022>

EV-T2M3SO12-4P-P-SET - Infrastructure charging socket

1164423

<https://www.phoenixcontact.com/us/products/1164423>



CHARX connect modular, Infrastructure charging socket, square, Premium, Set, with square protective cover, with temperature sensors, with LED (common cathode connection), for charging electric vehicles (EV) with alternating current (AC), Type 2, IEC 62196-2, 32 A / 480 V (AC), without single-core wires, locking actuator: 12 V, 4-pos., Rear panel mounting, M5 thread, housing: black, PHOENIX CONTACT logo

EV-T2M3SO12-3P-BL-SET - Infrastructure charging socket

1268358

<https://www.phoenixcontact.com/us/products/1268358>



CHARX connect modular, Infrastructure charging socket, square, Basic, Set, with square protective cover, with LED (common cathode connection), for charging electric vehicles (EV) with alternating current (AC), Type 2, IEC 62196-2, 32 A / 480 V (AC), without single-core wires, locking actuator: 12 V, 3-pos., Rear panel mounting, M5 thread, housing: black, PHOENIX CONTACT logo

CHARX SEC-3000 - AC charging controller



1139022

<https://www.phoenixcontact.com/us/products/1139022>

EV-T2M3SO12-4P-BL-SET - Infrastructure charging socket

1268355

<https://www.phoenixcontact.com/us/products/1268355>



CHARX connect modular, Infrastructure charging socket, square, Basic, Set, with square protective cover, with LED (common cathode connection), for charging electric vehicles (EV) with alternating current (AC), Type 2, IEC 62196-2, 32 A / 480 V (AC), without single-core wires, locking actuator: 12 V, 4-pos., Rear panel mounting, M5 thread, housing: black, PHOENIX CONTACT logo

EV-T2M3SO12-3P-B-SET - Infrastructure charging socket

1164420

<https://www.phoenixcontact.com/us/products/1164420>



CHARX connect modular, Infrastructure charging socket, square, Basic, Set, with square protective cover, for charging electric vehicles (EV) with alternating current (AC), Type 2, IEC 62196-2, 32 A / 480 V (AC), without single-core wires, locking actuator: 12 V, 3-pos., Rear panel mounting, M5 thread, housing: black, PHOENIX CONTACT logo

CHARX SEC-3000 - AC charging controller

1139022

<https://www.phoenixcontact.com/us/products/1139022>



EV-T2M3SO12-4P-B-SET - Infrastructure charging socket

1164417

<https://www.phoenixcontact.com/us/products/1164417>



CHARX connect modular, Infrastructure charging socket, square, Basic, Set, with square protective cover, for charging electric vehicles (EV) with alternating current (AC), Type 2, IEC 62196-2, 32 A / 480 V (AC), without single-core wires, locking actuator: 12 V, 4-pos., Rear panel mounting, M5 thread, housing: black, PHOENIX CONTACT logo

Phoenix Contact 2023 © - all rights reserved

<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com