

# WP 6215-WHPS - Web panel



1290809

<https://www.phoenixcontact.com/us/products/1290809>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



IP66 Touch panel with 21.5-inch widescreen (16:9) HD, PCAP display, Software: Qt Browser

## Your advantages

- Easy startup – just enter the IP and URL
- Flexible, thanks to open web standard and free choice of web server and visualization software
- No security updates are required for JAVA or Flash plug-ins thanks to HTML5
- Ideal for use with PLCnext Engineer or CODESYS
- Embedded Linux operating system
- Visualization of self-programmed JavaScript applications possible

## Commercial data

Item number	1290809
Packing unit	1 pc
Sales key	DR17
Product key	DRCADF
GTIN	4063151523138
Weight per piece (including packing)	2,260 g
Weight per piece (excluding packing)	2,100 g
Country of origin	TW

## Technical data

### Product properties

Product type	Operator panel
--------------	----------------

#### Computer data

Processor	Arm® Cortex®-A53, 1.6 GHz
Operating system	Yocto/Linux
Data storage system	Flash eMMC, 8 GB
Slots	1x microSD

#### Display

Display type	54.6 cm / 21.5" TFT
Screen resolution	1920 x 1080 Pixel(s) (Full HD)
Touch technology	projective-capacitive (PCAP)
Display lighting type	LED
Brightness	400 cd/m², typical (adjustable)
MTBF	50000 h
Color spectrum	16.7 million colors
Reading angle left	89 °
Reading angle right	89 °
Reading angle top	89 °
Reading angle bottom	89 °

### Software

User software	QT browser
---------------	------------

#### System requirements

Runtime system	Qt Browser
----------------	------------

### Interfaces

Interfaces	2x USB Host 2.0, 1x USB Type C 3.0 1x COM (RS-232/422/485)
Optional interfaces	Without optional interface
Network	1x Ethernet (10/100/1000 Mbps), RJ45
Bus system	without

### System properties

User software	QT browser
---------------	------------

#### System requirements

Runtime system	Qt Browser
----------------	------------

### Electrical properties

#### Supply

Supply voltage	24 V DC
Supply voltage range	18 V ... 32 V
Power supply unit	24 V DC $\pm 20$ %

## Real-time clock

Realtime clock	Integrated (battery backup)
----------------	-----------------------------

## Mounting

Mounting type	Front mounting
---------------	----------------

## Material specifications

Material front plate	Aluminum (natural anodized)
Housing material	Aluminum cast alloy, powder-coated

## Connection data

Connection method	Screw connection
Conductor cross section, rigid	0.2 mm <sup>2</sup> ... 2.5 mm <sup>2</sup>
Conductor cross section, flexible	0.2 mm <sup>2</sup> ... 2.5 mm <sup>2</sup>
Conductor cross section AWG	24 ... 12
Stripping length	7 mm

## Environmental and real-life conditions

### Ambient conditions

Degree of protection	IP66 (front), IP20 (back)
Ambient temperature (operation)	0 °C ... 50 °C
Ambient temperature (storage/transport)	-20 °C ... 60 °C
Permissible humidity (operation)	10 % ... 95 % (non-condensing)
Permissible humidity (storage/transport)	10 % ... 95 % (non-condensing)
Vibration (operation)	1g

## Dimensions

### External dimensions

Width / Height / Depth	532 mm / 346 mm / 51 mm (Dimensions of the front plate)
------------------------	---

### Installation dimensions

Width / Height / Installation depth	522 mm / 336 mm / (Installation cutout)
-------------------------------------	---

1290809

<https://www.phoenixcontact.com/us/products/1290809>

## Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/1290809>



**IECEE CB Scheme**

Approval ID: US-39088-UL



**EAC**

Approval ID: RU C-DE.A\*08.B01708



**UL Listed**

Approval ID: FILE E 238705



**cUL Listed**

Approval ID: FILE E 238705

**cULus Listed**

## Classifications

### ECLASS

ECLASS-11.0	27330201
ECLASS-12.0	27330201
ECLASS-13.0	27330201

### ETIM

ETIM 8.0	EC001412
----------	----------

### UNSPSC

UNSPSC 21.0	43211900
-------------	----------

# WP 6215-WHPS - Web panel

1290809

<https://www.phoenixcontact.com/us/products/1290809>



## Environmental product compliance

REACH SVHC	Lead 7439-92-1
------------	----------------

# WP 6215-WHPS - Web panel

1290809

<https://www.phoenixcontact.com/us/products/1290809>



## Accessories

### TP6/WP6/VL3 MOUNTING HW (2PCS) - Panel-mount flange

1289537

<https://www.phoenixcontact.com/us/products/1289537>

Mounting kit includes two retaining clips



---

### TP/WP 6000 RTC BATTERY KIT - Battery

1289761

<https://www.phoenixcontact.com/us/products/1289761>

Replacement battery for TP and WP 6000 touch panel



## WP 6215-WHPS - Web panel

1290809

<https://www.phoenixcontact.com/us/products/1290809>



## MSTB 2,5/ 3-STF-5,08 - PCB connector

1777992

<https://www.phoenixcontact.com/us/products/1777992>



PCB connector, nominal cross section: 2.5 mm<sup>2</sup>, color: green, nominal current: 12 A, rated voltage (III/2): 320 V, contact surface: Tin, contact connection type: Socket, number of potentials: 3, number of rows: 1, number of positions: 3, number of connections: 3, product range: MSTB 2,5/..-STF, pitch: 5.08 mm, connection method: Screw connection with tension sleeve, screw head form: L Slotted, conductor/PCB connection direction: 0 °, locking clip: - without locking clip, plug-in system: COMBICON MSTB 2,5, locking: Screw locking mechanism, mounting: Screw flange, type of packaging: packed in cardboard

---

## MICROSDHC-16GB - Memory

1154696

<https://www.phoenixcontact.com/us/products/1154696>



Industrial grade 16 GB MicroSDHC 3DTLC



# WP 6215-WHPS - Web panel

1290809

<https://www.phoenixcontact.com/us/products/1290809>



## MICROSDHC-32GB - Memory

1154699

<https://www.phoenixcontact.com/us/products/1154699>



Industrial grade 32 GB MicroSDHC 3DTLC

---

Phoenix Contact 2023 © - all rights reserved

<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)