

AI 4 -15 GY - Ferrule

1200264

<https://www.phoenixcontact.com/us/products/1200264>



Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Ferrule, sleeve length: 15 mm, length: 23 mm, color: gray

Your advantages

- The ferrules with plastic sleeve are made from soft tin-plated electrolytic copper
- The insulation reliability of close connections is increased and the splicing of wires is prevented

Commercial data

| | |
|--------------------------------------|---------------------|
| Item number | 1200264 |
| Packing unit | 1 pc |
| Minimum order quantity | 100 pc |
| Sales key | BH34 |
| Product key | BH3411 |
| Catalog page | Page 481 (C-3-2019) |
| GTIN | 4055626313658 |
| Weight per piece (including packing) | 0.362 g |
| Weight per piece (excluding packing) | 0.362 g |
| Customs tariff number | 85369010 |
| Country of origin | DE |

Technical data

Product properties


| | |
|--------------------|---|
| Product type | Cable end sleeve |
| Conductor category | stranded conductors, class 2, 5, 6 / B, C, K, M |

Connection data

Conductor connection

| | |
|---------------------------------------|-------------------|
| Conductor cross section flexible max. | 4 mm ² |
| Conductor cross section AWG max. | 12 |
| Stripping length | 18 mm |

Dimensions

| | |
|---|---|
| Dimensional drawing |  |
| Length | 23 mm |
| Sleeve length | 15 mm |
| Maximum stripping length | 18 mm |
| Ferrule diameter | 2.8 mm |
| Sleeve wall thickness | 0.2 mm |
| Insulating collar thickness | 0.3 mm |
| Inner dimensions of the insulating collar | 4.8 mm |

Material specifications

| | |
|--|--------------------------------|
| Color | gray |
| Material | CU-DHP |
| Flammability rating according to UL 94 | HB |
| Coating | tin-plated (galvanic) |
| Components | free from silicone and halogen |

Mechanical properties

Technical data

| | |
|---------------|-------|
| Sleeve length | 15 mm |
|---------------|-------|

Environmental and real-life conditions

Ambient conditions

| | |
|------------------------|---|
| Permanent temperature | 105 °C (-40 °C no load / 0 °C dynamic load) |
| Short-term temperature | 120 °C |

AI 4 -15 GY - Ferrule


1200264

<https://www.phoenixcontact.com/us/products/1200264>



Drawings

Dimensional drawing



AI 4 -15 GY - Ferrule

1200264

<https://www.phoenixcontact.com/us/products/1200264>



Classifications

ECLASS

| | |
|-------------|----------|
| ECLASS-11.0 | 27400201 |
| ECLASS-12.0 | 27400201 |
| ECLASS-13.0 | 27400201 |

ETIM

| | |
|----------|----------|
| ETIM 8.0 | EC000005 |
|----------|----------|

UNSPSC

| | |
|-------------|----------|
| UNSPSC 21.0 | 27121700 |
|-------------|----------|

AI 4 -15 GY - Ferrule



1200264
<https://www.phoenixcontact.com/us/products/1200264>

Environmental product compliance

| | |
|------------|---|
| China RoHS | Environmentally friendly use period: unlimited = EFUP-e |
| | No hazardous substances above threshold values |

Phoenix Contact 2023 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com