

CUC-USB3.0-J1ST-AH/UAF-THT - USB PCB connectors



1332637
<https://www.phoenixcontact.com/us/products/1332637>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



USB PCB connectors, degree of protection: IP20, number of positions: 9, 5 Gbps, material: Metal, connection method: Solder connection, cable outlet: straight, USB 3.0

Your advantages

- Optimized for wave soldering
- Data transmission up to 5 Gbps
- Comfortable tray packing

Commercial data

Item number	1332637
Packing unit	1 pc
Minimum order quantity	117 pc
Sales key	AB14
Product key	ABNDAB
GTIN	4063151629663
Weight per piece (including packing)	3.71 g
Weight per piece (excluding packing)	3.71 g
Customs tariff number	85366990
Country of origin	CN

CUC-USB3.0-J1ST-AH/UAF-THT - USB PCB connectors



1332637

<https://www.phoenixcontact.com/us/products/1332637>

Technical data

Product properties

Type	USB-A
Product type	Data connector (device side)
Sensor type	USB 3.0
Number of positions	9
Type of packaging	Tray
Connection profile	USB-A
Number of slots	1
Type	Socket
Shielded	yes
Cable outlet	straight

Insulation characteristics

Overvoltage category	I
Degree of pollution	2

Electrical properties

Rated voltage (III/2)	30 V
Rated surge voltage (III/2)	1500 V
Rated current	1.8 A
Contact resistance	30 mΩ
Frequency range	20 Hz ... 500 Hz
Insulation resistance	1000 MΩ
Transmission medium	Copper
Transmission characteristics (category)	USB 3.2 Gen 1
Transmission speed	5 GBit/s
Power transmission	54 W

Connection data

Connection technology

Connection method	Solder connection
-------------------	-------------------

Dimensions

Width	14.4 mm
Height	7.74 mm
Length	16.5 mm
Orientation to	90.00 °

Material specifications

Color of the housing part	blue
Flammability rating according to UL 94	V0
Contact material	Copper alloy

CUC-USB3.0-J1ST-AH/UAF-THT - USB PCB connectors



1332637

<https://www.phoenixcontact.com/us/products/1332637>

Contact surface material	Gold over nickel
Contact carrier material	PA 4T
Housing material	Metal

Cable/line

Test voltage Core/Core	500 V
Test voltage Core/Shield	500 V
Acceleration	3.1 m/s ²
Halogen-free	yes

Mechanical properties

Mechanical data

Insertion/withdrawal cycles	> 5000
Insertion force per signal contact	35.00 N
Extraction force per signal contact	< 10 N

Environmental and real-life conditions

Test specification

Specification	EIA 364-1000
Frequency	20-500 Hz
Sweep speed	1 octave/min
Acceleration	3.1 m/s ²
Test duration	15 min.
Contact resistance R ₁	30 mΩ

Test specification

Specification	60068-2-27
Acceleration	30 g
Number of shocks per direction	18

Ambient conditions

Degree of protection	IP20
Ambient temperature (operation)	-55 °C ... 85 °C

Mounting

Mounting type	Wave soldering
Connection method	Solder connection

Processing notes

Process	Wave soldering
Classification temperature T _c	260 °C

CUC-USB3.0-J1ST-AH/UAF-THT - USB PCB connectors



1332637

<https://www.phoenixcontact.com/us/products/1332637>

Classifications

ECLASS

ECLASS-11.0	27440390
ECLASS-12.0	27440390
ECLASS-13.0	27440390

ETIM

ETIM 8.0	EC001121
----------	----------

UNSPSC

UNSPSC 21.0	39121400
-------------	----------

CUC-USB3.0-J1ST-AH/UAF-THT - USB PCB connectors



1332637
<https://www.phoenixcontact.com/us/products/1332637>

Environmental product compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Phoenix Contact 2023 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com