

SACC-VB-5CON-M20/AD-2L 24V - Valve connectors



1457908

<https://www.phoenixcontact.com/us/products/1457908>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Valve connectors, Universal, 5-position, Valve connector AD (pressure switch), Screw connection, cable gland M16, external cable diameter 6 mm ... 8 mm

Commercial data

Item number	1457908
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	BF36
Product key	BF2DAA
Catalog page	Page 29 (C-2-2019)
GTIN	4046356630689
Weight per piece (including packing)	32.9 g
Weight per piece (excluding packing)	32.3 g
Customs tariff number	85366990
Country of origin	HU

Technical data

Notes

General

NOTE: Observe the permissible bending radii when laying conductors, since the degree of protection may be put in jeopardy if the bending forces are too high. Alleviate mechanical loads upstream of the connector, e.g. by using cable ties.

Mounting

Connection method

Screw connection

Product properties

Sensor type

Universal

Number of positions

5

No. of cable outlets

1

Shielded

no

Pg screw connection

M16

Insulation characteristics

Overvoltage category

II

Degree of pollution

3

Material specifications

Flammability rating according to UL 94

HB

Seal material

NBR

Material housing valve plug

PA

Contact material

CuZn

Contact surface material

CuSn

Dimensions

External dimensions

Outside diameter

6 mm ... 8 mm

Electrical properties

Contact resistance

≤ 4 mΩ

Insulation resistance

> 2 GΩ

Nominal voltage U_N

24 V AC

24 V DC

Nominal current I_N

1.5 A

Protective circuit

unwired

Valve connector characteristics

Fixing screws

M3 x 37,5

Mechanical properties

SACC-VB-5CON-M20/AD-2L 24V - Valve connectors



1457908

<https://www.phoenixcontact.com/us/products/1457908>

Mechanical data

Insertion/withdrawal cycles	50 (Valve connector)
-----------------------------	----------------------

Signaling

Status display	2 LEDs
Status display present	Yes

Connection data

Connection method	Screw connection
Conductor cross section	0.25 mm² ... 1.5 mm²
Connection cross section AWG	24 ... 16
Tightening torque	1.8 Nm ±0.2 Nm (Pressure screw)
	0.4 Nm ±0.1 Nm (Central screw)
	0.2 Nm ±0.1 Nm (Contact screw)

Connector

Connection 1

Head design	Valve connector
Head thread type	AD (pressure switch)

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP65
Ambient temperature (operation)	-25 °C ... 60 °C (valve plug)


Standards and regulations

Valve connector


Standard designation	Valve connector
Standards/specifications	EN 175301-803

Drawings

Dimensional drawing



Circuit diagram



SACC-VB-5CON-M20/AD-2L 24V - Valve connectors



1457908

<https://www.phoenixcontact.com/us/products/1457908>

Classifications

ECLASS

ECLASS-11.0	27440105
ECLASS-12.0	27440105
ECLASS-13.0	27440105

ETIM

ETIM 8.0	EC003623
----------	----------

UNSPSC

UNSPSC 21.0	31251500
-------------	----------

Environmental product compliance

REACH SVHC	Lead 7439-92-1
China RoHS	Environmentally Friendly Use Period = 25;
	For information on hazardous substances, refer to the manufacturer's declaration available under "Downloads"

SACC-VB-5CON-M20/AD-2L 24V - Valve connectors



1457908

<https://www.phoenixcontact.com/us/products/1457908>

Accessories

SAC-5P-100,0-PUR/0,5 - Cable reel

1457403

<https://www.phoenixcontact.com/us/products/1457403>



By the meter, Cable reel, PUR halogen-free, black-gray RAL 7021, 5-wire, color single wire: black 1, black 2, black 3, black 4, green/yellow, cable length: 100 m

Phoenix Contact 2023 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com