

MBK 10 - Mini feed-through terminal block



1402018

<https://www.phoenixcontact.com/us/products/1402018>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Mini feed-through terminal block, nom. voltage: 500 V, nominal current: 61 A, number of connections: 2, connection method: Screw connection, 1 level, cross section: 0.5 mm² - 10 mm², mounting type: NS 15, color: gray

Your advantages

- Space saving thanks to compact design and mounting option on a 15 mm DIN rail
- Clear arrangement thanks to marking of all terminal points
- Easy potential distribution thanks to standardized plug-in bridges

Commercial data

Item number	1402018
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	BE12
Product key	BE1261
GTIN	4017918020750
Weight per piece (including packing)	14.24 g
Weight per piece (excluding packing)	13.303 g
Customs tariff number	85369010
Country of origin	DE

MBK 10 - Mini feed-through terminal block



1402018

<https://www.phoenixcontact.com/us/products/1402018>

Technical data

Product properties

Product type	Miniature terminal block
Number of connections	2
Number of rows	1

Electrical properties

Maximum power dissipation for nominal condition	0 W
---	-----

Connection data

Number of connections per level	2
---------------------------------	---

1 level

Tightening torque	1.5 ... 1.8 Nm
Stripping length	10 mm
Connection in acc. with standard	IEC 60947-7-1
Conductor cross section rigid	0.5 mm ² ... 10 mm ²
Cross section AWG	20 ... 8 (converted acc. to IEC)
Conductor cross section flexible	0.5 mm ² ... 6 mm ²
Conductor cross section, flexible [AWG]	20 ... 10 (converted acc. to IEC)
Flexible conductor cross section (ferrule with plastic sleeve)	0.5 mm ² ... 6 mm ²
Nominal current	61 A
Nominal voltage	500 V

Dimensions

Width	7.5 mm
-------	--------

Material specifications

Color	gray
Flammability rating according to UL 94	V0
Insulating material	PA
Static insulating material application in cold	-60 °C
Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21))	125 °C
Relative insulation material temperature index (Elec., UL 746 B)	130 °C
Fire protection for rail vehicles (DIN EN 45545-2) R22	HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R23	HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R24	HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R26	HL 1 - HL 3
Calorimetric heat release NFPA 130 (ASTM E 1354)	27,5 MJ/kg
Surface flammability NFPA 130 (ASTM E 162)	passed
Specific optical density of smoke NFPA 130 (ASTM E 662)	passed
Smoke gas toxicity NFPA 130 (SMP 800C)	passed

MBK 10 - Mini feed-through terminal block



1402018

<https://www.phoenixcontact.com/us/products/1402018>

Electrical tests

Surge voltage test

Test voltage setpoint	7.3 kV
Result	Test passed

Temperature-rise test

Requirement temperature-rise test	Increase in temperature ≤ 45 K
Result	Test passed
Short-time withstand current 6 mm ²	0.72 kA
Short-time withstand current 10 mm ²	1.2 kA
Result	Test passed

Power-frequency withstand voltage

Test voltage setpoint	1.89 kV
Result	Test passed

Mechanical properties

Mechanical data

Open side panel	No
-----------------	----

Mechanical tests

Mechanical strength

Result	Test passed
--------	-------------

Attachment on the carrier

DIN rail/fixing support	NS 15
Test force setpoint	5 N
Result	Test passed

Test for conductor damage and slackening

Rotation speed	10 rpm
Revolutions	135
Conductor cross section/weight	0.5 mm ² / 0.3 kg
	6 mm ² / 1.4 kg
	10 mm ² / 2 kg
Result	Test passed

Environmental and real-life conditions

Needle-flame test

Time of exposure	30 s
Result	Test passed

Ambient conditions

MBK 10 - Mini feed-through terminal block



1402018

<https://www.phoenixcontact.com/us/products/1402018>

Ambient temperature (storage/transport)	-25 °C ... 60 °C (for a short time, not exceeding 24 h, -60 °C to +70 °C)
Ambient temperature (assembly)	-5 °C ... 70 °C
Ambient temperature (actuation)	-5 °C ... 70 °C
Permissible humidity (storage/transport)	30 % ... 70 %

Standards and regulations

Connection in acc. with standard	IEC 60947-7-1
----------------------------------	---------------

Mounting

Mounting type	NS 15
---------------	-------

MBK 10 - Mini feed-through terminal block




1402018


<https://www.phoenixcontact.com/us/products/1402018>


Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/1402018>

 CSA Approval ID: 13631				
	Nominal voltage U_N	Nominal current I_N	Cross section AWG	Cross section mm^2
	300 V	55 A	26 - 8	-

 EAC Approval ID: RU C-DE.AI30.B.01102				
---	--	--	--	--

 cULus Recognized Approval ID: E60425				
	Nominal voltage U_N	Nominal current I_N	Cross section AWG	Cross section mm^2
Use group B				
	600 V	50 A	26 - 8	-
Use group C				
	600 V	50 A	26 - 8	-

 ClassNK Approval ID: 09 ME 142				
--	--	--	--	--

 EAC Approval ID: RU C-DE.BL08.B.00534				
---	--	--	--	--

MBK 10 - Mini feed-through terminal block



1402018

<https://www.phoenixcontact.com/us/products/1402018>

Classifications

ECLASS

ECLASS-11.0	27141120
ECLASS-13.0	27250101

ETIM

ETIM 8.0	EC000897
----------	----------

UNSPSC

UNSPSC 21.0	39121400
-------------	----------

MBK 10 - Mini feed-through terminal block



1402018

<https://www.phoenixcontact.com/us/products/1402018>

Environmental product compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

MBK 10 - Mini feed-through terminal block

1402018

<https://www.phoenixcontact.com/us/products/1402018>



Accessories

EB 2- BK 4 - Insertion bridge

0801157

<https://www.phoenixcontact.com/us/products/0801157>

Insertion bridge, 2-pos., for strip terminal block, BK 4



EB 3- BK 4 - Insertion bridge

0801144

<https://www.phoenixcontact.com/us/products/0801144>

Insertion bridge, 3-pos., for strip terminal block, BK 4



MBK 10 - Mini feed-through terminal block

1402018


<https://www.phoenixcontact.com/us/products/1402018>



EB 10- BK 4 - Insertion bridge

0801131

<https://www.phoenixcontact.com/us/products/0801131>



Insertion bridge, 10-pos., for strip terminal block, BK 4

ATP-MBK - Partition plate

1413227

<https://www.phoenixcontact.com/us/products/1413227>



Partition plate, length: 42.5 mm, width: 2.5 mm, height: 42.5 mm, color: gray

MBK 10 - Mini feed-through terminal block



1402018

<https://www.phoenixcontact.com/us/products/1402018>

BN-ZB 7,5/WH-100:UNBEDRUCKT - Marker pin Zack strip

5060854

<https://www.phoenixcontact.com/us/products/5060854>



Marker pin Zack strip, Strip, white, unlabeled, can be labeled with: CMS-P1-PLOTTER, mounting type: plug in, for terminal block width: 7.5 mm, lettering field size: 6 x 4 mm, Number of individual labels: 1000

BN-ZB 7,5/WH:UNBEDRUCKT - Marker pin Zack strip

1401844

<https://www.phoenixcontact.com/us/products/1401844>



Marker pin Zack strip, Strip, white, unlabeled, can be labeled with: CMS-P1-PLOTTER, mounting type: plug in, for terminal block width: 7.5 mm, lettering field size: 6 x 4 mm, Number of individual labels: 10

MBK 10 - Mini feed-through terminal block

1402018

<https://www.phoenixcontact.com/us/products/1402018>



BN-ZB 7,5/WH CUS - Marker pin Zack strip

0824278

<https://www.phoenixcontact.com/us/products/0824278>



Marker pin Zack strip, can be ordered: Strip, white, labeled according to customer specifications, mounting type: plug in, for terminal block width: 7.5 mm, lettering field size: 6 x 4 mm

SZS 1,0X4,0 VDE - Screwdriver

1205066

<https://www.phoenixcontact.com/us/products/1205066>



Screwdriver, slot-headed, VDE insulated, size: 1.0 x 4.0 x 100 mm, 2-component grip, with non-slip grip

MBK 10 - Mini feed-through terminal block



1402018

<https://www.phoenixcontact.com/us/products/1402018>

NS 15 UNPERF 2000MM VPE 10 - DIN rail, unperforated

1401695

<https://www.phoenixcontact.com/us/products/1401695>



DIN rail, unperforated, acc. to EN 60715, material: Steel, galvanized, passivated with a thick layer, Standard profile, color: silver, Pack of 10 (20 m)

NS 15 PERF 2000MM VPE 10 - DIN rail perforated

1401682

<https://www.phoenixcontact.com/us/products/1401682>



DIN rail perforated, acc. to EN 60715, material: Steel, galvanized, passivated with a thick layer, Standard profile, color: silver, Pack of 10 (20 m)

MBK 10 - Mini feed-through terminal block

1402018

<https://www.phoenixcontact.com/us/products/1402018>



NS 15 AL PERF 2000MM VPE 10 - DIN rail perforated

1401763

<https://www.phoenixcontact.com/us/products/1401763>



DIN rail perforated, acc. to EN 60715, material: Aluminum, uncoated, Standard profile, color: silver, Pack of 10 (20 m)

NS 15 WH PERF 2000MM-VPE 10 - DIN rail perforated

1204096

<https://www.phoenixcontact.com/us/products/1204096>



DIN rail perforated, acc. to EN 60715, material: Steel, Galvanized, white passivated, Standard profile, color: silver, Pack of 10 (20 m)

MBK 10 - Mini feed-through terminal block

1402018


<https://www.phoenixcontact.com/us/products/1402018>



E/MBK - End clamp

1401637

<https://www.phoenixcontact.com/us/products/1401637>



End clamp, width: 6.2 mm, color: gray

E/MK - End clamp

1421633

<https://www.phoenixcontact.com/us/products/1421633>



End clamp, width: 6.2 mm, color: gray

MBK 10 - Mini feed-through terminal block

1402018

<https://www.phoenixcontact.com/us/products/1402018>




E/MK 1 - End clamp

1421659

<https://www.phoenixcontact.com/us/products/1421659>

End clamp width: 6 mm, color: gray



Phoenix Contact 2023 © - all rights reserved

<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com