

MBK-FS/FS - Mini feed-through terminal block



1406014

<https://www.phoenixcontact.com/us/products/1406014>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Mini feed-through terminal block, nom. voltage: 400 V, nominal current: 16 A, 1 level, connection method: Spade connection, cross section: 0.5 mm² - 1 mm², mounting: NS 15, color: gray

Your advantages

- Clear arrangement thanks to marking of all terminal points
- Space saving thanks to compact design and mounting option on a 15 mm DIN rail
- Easy potential distribution thanks to standardized plug-in bridges

Commercial data

Item number	1406014
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	BE05
Product key	BE511X
Catalog page	Page 313 (CL-2005)
GTIN	4017918021023
Weight per piece (including packing)	2.3 g
Weight per piece (excluding packing)	2.085 g
Customs tariff number	85369010
Country of origin	DE

MBK-FS/FS - Mini feed-through terminal block



1406014

<https://www.phoenixcontact.com/us/products/1406014>

Technical data

Product properties

Product type	Miniature terminal block
Number of connections	8
Number of rows	1
Potentials	1

Insulation characteristics

Overvoltage category	III
Degree of pollution	3

Electrical properties

Rated surge voltage	6 kV
Maximum power dissipation for nominal condition	0 W

Connection data

Number of connections per level	2
---------------------------------	---

1 level

Spade connection	6.3/2.8 x 0.8 mm
Connection in acc. with standard	IEC 60947-7-1
Conductor cross section rigid	0.5 mm ² ... 1 mm ²
Cross section AWG	20 ... 14 (converted acc. to IEC)
Conductor cross section flexible	0.5 mm ² ... 1 mm ²
Conductor cross section, flexible [AWG]	20 ... 18 (converted acc. to IEC)
Flexible conductor cross section (ferrule with plastic sleeve)	0.5 mm ² ... 1 mm ²
Nominal current	16 A (current data for slip-on connections in acc. with DIN 61210 are also dependent on nominal size, material, insulation of the sleeve and conductor cross section.)
Maximum load current	16 A (current data for slip-on connections in acc. with DIN 61210 are also dependent on nominal size, material, insulation of the sleeve and conductor cross section.)
Nominal voltage	400 V (voltage data for slip-on connections in acc. with DIN 61210 are also dependent on nominal size, material, insulation of the sleeve and conductor cross section.)

Dimensions

Width	5.2 mm
-------	--------

Material specifications

Color	gray
Flammability rating according to UL 94	V2
Insulating material group	I
Insulating material	PA
Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21))	125 °C

MBK-FS/FS - Mini feed-through terminal block



1406014

<https://www.phoenixcontact.com/us/products/1406014>

Relative insulation material temperature index (Elec., UL 746 B)	125 °C
--	--------

Mechanical properties

Mechanical data

Open side panel	No
-----------------	----

Environmental and real-life conditions

Ambient conditions

Ambient temperature (operation)	-60 °C ... 105 °C (max. short-term operating temperature RTI Elec.)
Ambient temperature (storage/transport)	-25 °C ... 60 °C (for a short time, not exceeding 24 h, -60 °C to +70 °C)
Ambient temperature (assembly)	-5 °C ... 70 °C
Ambient temperature (actuation)	-5 °C ... 70 °C
Permissible humidity (storage/transport)	30 % ... 70 %

Standards and regulations

Connection in acc. with standard	IEC 60947-7-1
----------------------------------	---------------

Mounting

Mounting type	NS 15
---------------	-------

MBK-FS/FS - Mini feed-through terminal block




1406014

<https://www.phoenixcontact.com/us/products/1406014>

Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/1406014>

 CSA Approval ID: 13631				
	Nominal voltage U _N	Nominal current I _N	Cross section AWG	Cross section mm ²
	150 V	20 A	22 - 14	-

 EAC Approval ID: RU C-DE.BL08.B.00541				
---	--	--	--	--

MBK-FS/FS - Mini feed-through terminal block



1406014

<https://www.phoenixcontact.com/us/products/1406014>

Classifications

ECLASS

ECLASS-11.0	27141120
ECLASS-13.0	27250101

ETIM

ETIM 8.0	EC000897
----------	----------

UNSPSC

UNSPSC 21.0	39121400
-------------	----------

MBK-FS/FS - Mini feed-through terminal block



1406014

<https://www.phoenixcontact.com/us/products/1406014>

Environmental product compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Phoenix Contact 2023 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com