

# A-INL-M50-P-GY - Counter nut



1411211

<https://www.phoenixcontact.com/us/products/1411211>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

Counter nut, for threads M50 x 1.5, color: silver-grey RAL 7001



## Commercial data

|                                      |                     |
|--------------------------------------|---------------------|
| Item number                          | 1411211             |
| Packing unit                         | 1 pc                |
| Minimum order quantity               | 5 pc                |
| Sales key                            | BF68                |
| Product key                          | BF7DZX              |
| Catalog page                         | Page 686 (C-2-2019) |
| GTIN                                 | 4046356923439       |
| Weight per piece (including packing) | 11.31 g             |
| Weight per piece (excluding packing) | 11.31 g             |
| Customs tariff number                | 39269097            |
| Country of origin                    | TR                  |

# A-INL-M50-P-GY - Counter nut

1411211


<https://www.phoenixcontact.com/us/products/1411211>

## Technical data

### Product properties

|              |          |
|--------------|----------|
| Product type | Flat nut |
| Thread type  | M50      |

### Dimensions

|                             |  |
|-----------------------------|--|
| Dimensional drawing         |  |
| Length                      | 8 mm   |
| Diameter                    | 50 mm  |
| Connecting thread diameter  | 50 mm  |
| Wrench size, counter nut    | 60 mm  |
| Hexagon angular dimension   | 66.1 mm  |
| Thread type connection side | M50 x 1.5  |
| Thread pitch                | 1.5 mm   |

### Material specifications

|  |    |
|--|----|
| Material                               | PA |
| Flammability rating according to UL 94 | V2 |

### Cable/line

|              |     |
|--------------|-----|
| Halogen-free | yes |
|--------------|-----|

### Environmental and real-life conditions

#### Ambient conditions

|                                 |                   |
|---------------------------------|-------------------|
| Ambient temperature (operation) | -40 °C ... 100 °C |
|---------------------------------|-------------------|

# A-INL-M50-P-GY - Counter nut


1411211

<https://www.phoenixcontact.com/us/products/1411211>



## Drawings

Dimensional drawing



Dimensional drawing

# A-INL-M50-P-GY - Counter nut



1411211

<https://www.phoenixcontact.com/us/products/1411211>

## Classifications

### ECLASS

|             |          |
|-------------|----------|
| ECLASS-11.0 | 27144424 |
| ECLASS-13.0 | 27140807 |

### ETIM

|          |          |
|----------|----------|
| ETIM 8.0 | EC000940 |
|----------|----------|

### UNSPSC

|             |          |
|-------------|----------|
| UNSPSC 21.0 | 31161700 |
|-------------|----------|

# A-INL-M50-P-GY - Counter nut



1411211

<https://www.phoenixcontact.com/us/products/1411211>

## Environmental product compliance

|            |   |
|------------|---|
| China RoHS | Environmentally friendly use period: unlimited = EFUP-e |
|            | No hazardous substances above threshold values          |

Phoenix Contact 2023 © - all rights reserved  
<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)