

SACC-CIP-M8MS-3P SMD SH R32 - Contact carrier



1412263

<https://www.phoenixcontact.com/us/products/1412263>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Contact carrier, 3-position, Pin, straight, M8, coding: A, PCB mounting, SMD reflow, Alternative product in accordance with RoHS II without Exemption 6c (Pb <0.1%) item no.: 1308281

Your advantages

- Reduced mounting costs thanks to two-piece device connector
- Packaging available for automated pick and place assembly
- All common pin assignments and codings available
- Easy device integration thanks to mechanical port screw connections with threaded attachment, press-in contour or direct integration in the front plate
- Optional shield connection and seal for the device when not plugged in

Commercial data

| | |
|--------------------------------------|---------------|
| Item number | 1412263 |
| Packing unit | 1 pc |
| Minimum order quantity | 100 pc |
| Sales key | AB22 |
| Product key | ABQHCB |
| GTIN | 4046356989046 |
| Weight per piece (including packing) | 5.5 g |
| Weight per piece (excluding packing) | 5.5 g |
| Customs tariff number | 85366990 |
| Country of origin | DE |

Technical data

Notes

| | |
|---------|--|
| General | The electrical and mechanical data specified assume that the connector pair is correctly locked and mounted. If the connector is unlocked and if there is a danger of contamination, the connector must be sealed using a protective cap > IP54. Influences arising from litz wires, cables or PCB assembly must also be taken into consideration. |
|---------|--|

Product properties

| | |
|---------------------|----------------|
| Product type | Contact insert |
| Number of positions | 3 |
| Application | Signal |
| Seal present | yes |
| Shielded | yes |
| Coding | A |
| Thread type | M8 |

Insulation characteristics

| | |
|----------------------|-----|
| Overvoltage category | III |
|----------------------|-----|

Electrical properties

| | |
|-----------------------|----------------------------|
| Contact resistance | $\leq 3 \text{ m}\Omega$ |
| Insulation resistance | $\leq 100 \text{ M}\Omega$ |
| Nominal voltage U_N | 48 V AC 60 V DC |
| Nominal current I_N | 4 A |

Material specifications

| | |
|--|------|
| Flammability rating according to UL 94 | V0 |
| Seal material | FKM |
| Contact material | CuZn |
| Contact surface material | Au |
| Contact carrier material | PA |

Connector

Connection 1

| | |
|-------------------|----------|
| Head design | Pin |
| Head cable outlet | straight |
| Head thread type | M8 |
| Coding | A |

Mechanical properties

Mechanical data

SACC-CIP-M8MS-3P SMD SH R32 - Contact carrier



1412263

<https://www.phoenixcontact.com/us/products/1412263>

| | |
|-----------------------------|-------|
| Insertion/withdrawal cycles | > 100 |
|-----------------------------|-------|

Environmental and real-life conditions

Ambient conditions

| | |
|--|---|
| Degree of protection (when plugged in) | IP67 (correctly plugged in and locked) |
| Degree of protection | IP67 |
| Ambient temperature (operation) | -40 °C ... 105 °C (Plug / socket) -55 °C ... 105 °C (without mechanical actuation) |

Standards and regulations

| | |
|--------------------------|-----------------|
| Standard designation | M8 connector |
| Standards/specifications | IEC 61076-2-104 |

Mounting

| | |
|-------------------|--------------|
| Mounting type | PCB mounting |
| Connection method | SMD reflow |

Packaging specifications

| | |
|-------------------|-------------------|
| Type of packaging | Belt |
| Delivery state | with assembly pad |

SACC-CIP-M8MS-3P SMD SH R32 - Contact carrier



1412263

<https://www.phoenixcontact.com/us/products/1412263>

Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/1412263>

| | | | | |
|--|-----------------------|-----------------------|-------------------|-----------------------------|
|  cULus Recognized Approval ID: E221474-20160506 | Nominal voltage U_N | Nominal current I_N | Cross section AWG | Cross section mm^2 |
| | 60 V | 3 A | - | - |

SACC-CIP-M8MS-3P SMD SH R32 - Contact carrier



1412263

<https://www.phoenixcontact.com/us/products/1412263>

Classifications

ECLASS

| | |
|-------------|----------|
| ECLASS-11.0 | 27440102 |
| ECLASS-12.0 | 27440116 |
| ECLASS-13.0 | 27440116 |

ETIM

| | |
|----------|----------|
| ETIM 8.0 | EC002635 |
|----------|----------|

UNSPSC

| | |
|-------------|----------|
| UNSPSC 21.0 | 39121400 |
|-------------|----------|

SACC-CIP-M8MS-3P SMD SH R32 - Contact carrier



1412263

<https://www.phoenixcontact.com/us/products/1412263>

Environmental product compliance

| | |
|------------|--|
| REACH SVHC | Lead 7439-92-1 |
| China RoHS | Environmentally Friendly Use Period = 50 years |
| | For information on hazardous substances, refer to the manufacturer's declaration available under "Downloads" |

Phoenix Contact 2023 © - all rights reserved

<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com