

SACC-CI-M8FS-3P SMD T - Contact carrier



1412220

<https://www.phoenixcontact.com/us/products/1412220>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Contact carrier, 3-position, Socket, straight, M8, coding: A, PCB mounting, SMD reflow, Alternative product in accordance with RoHS II without Exemption 6c (Pb <0.1%) item no.: 1238974

Your advantages

- Reduced mounting costs thanks to two-piece device connector
- Packaging available for automated pick and place assembly
- All common pin assignments and codings available
- Easy device integration thanks to mechanical port screw connections with threaded attachment, press-in contour or direct integration in the front plate
- Optional shield connection and seal for the device when not plugged in

Commercial data

Item number	1412220
Packing unit	1 pc
Minimum order quantity	60 pc
Sales key	AB22
Product key	ABQHCS
GTIN	4046356988308
Weight per piece (including packing)	2.733 g
Weight per piece (excluding packing)	2.57 g
Customs tariff number	85366990
Country of origin	DE

SACC-CI-M8FS-3P SMD T - Contact carrier



1412220

<https://www.phoenixcontact.com/us/products/1412220>

Technical data

Product properties

Product type	Contact insert
Number of positions	3
Application	Signal
Seal present	no
Shielded	no
Coding	A
Thread type	M8

Insulation characteristics

Overvoltage category	III
----------------------	-----

Electrical properties

Contact resistance	$\leq 3 \text{ m}\Omega$
Insulation resistance	$\geq 100 \text{ M}\Omega$
Nominal voltage U_N	48 V AC
	60 V DC
Nominal current I_N	4 A

Material specifications

Flammability rating according to UL 94	V0
----------------------------------------	----

Connector

Connection 1

Head design	Socket
Head cable outlet	straight
Head thread type	M8
Coding	A

Mechanical properties

Mechanical data

Insertion/withdrawal cycles	> 100
-----------------------------	-------

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP67, when plugged in
----------------------	-----------------------

Mounting

Mounting type	PCB mounting
Connection method	SMD reflow

SACC-CI-M8FS-3P SMD T - Contact carrier



1412220

<https://www.phoenixcontact.com/us/products/1412220>

Packaging specifications

Type of packaging	Tray
-------------------	------

SACC-CI-M8FS-3P SMD T - Contact carrier



1412220

<https://www.phoenixcontact.com/us/products/1412220>

Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/1412220>



EAC

Approval ID: B.01687



cULus Recognized

Approval ID: E221474-20160506

	Nominal voltage U_N	Nominal current I_N	Cross section AWG	Cross section mm^2
	60 V	3 A	-	-

SACC-CI-M8FS-3P SMD T - Contact carrier



1412220

<https://www.phoenixcontact.com/us/products/1412220>

Classifications

ECLASS

ECLASS-11.0	27440102
ECLASS-12.0	27440116
ECLASS-13.0	27440116

ETIM

ETIM 8.0	EC002635
----------	----------

UNSPSC

UNSPSC 21.0	39121400
-------------	----------

SACC-CI-M8FS-3P SMD T - Contact carrier



1412220

<https://www.phoenixcontact.com/us/products/1412220>

Environmental product compliance

REACH SVHC	Lead 7439-92-1
China RoHS	Environmentally Friendly Use Period = 50 years
	For information on hazardous substances, refer to the manufacturer's declaration available under "Downloads"

Phoenix Contact 2023 © - all rights reserved

<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com