

# SAC-3P-M12MR-M12FR SH/.../... - Sensor/actuator cable



1536078

<https://www.phoenixcontact.com/us/products/1536078>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Sensor/actuator cable, 3-position, Variable cable type, shielded, Plug angled M12, coding: A, connected with unwired, on Socket angled M12, coding: A, cable length: Free input (0.2 ... 40.0 m)

## Your advantages

- Easy and safe: 100% electrically tested plug-in components
- Reliable signal transmission – 360° shielding in environments with electromagnetic interference

## Commercial data

Item number	1536078
Packing unit	1 pc
Minimum order quantity	1 pc
Note	Made to order (non-returnable)
Sales key	BF17
Product key	BF1CIA
Catalog page	Page 193 (C-2-2019)
Customs tariff number	85444290
Country of origin	PL

# SAC-3P-M12MR-M12FR SH/.../... - Sensor/actuator cable



1536078

<https://www.phoenixcontact.com/us/products/1536078>

## Technical data

### Product properties

Product type	Sensor/actuator cable
Number of positions	3
Application	Standard
No. of cable outlets	1
Shielded	yes
Coding	A

### Insulation characteristics

Overvoltage category	II
Degree of pollution	3

### Material specifications

Flammability rating according to UL 94	HB
Seal material	NBR
Material of grip body	TPU, hardly inflammable, self-extinguishing
Contact material	CuSn
Contact surface material	Ni/Au
Contact carrier material	TPU GF
Material for screw connection	Zinc die-cast, nickel-plated

### Electrical properties

Contact resistance	$\leq 5 \text{ m}\Omega$
Insulation resistance	$\geq 100 \text{ M}\Omega$
Nominal voltage $U_N$	48 V AC
	60 V DC
Nominal current $I_N$	4 A
Test voltage	2500 V
Protective circuit	unwired

### Mechanical properties

#### Mechanical data

Insertion/withdrawal cycles	$\geq 100$
-----------------------------	------------

### Signaling

Status display	No
Status display present	No

### Connection data

#### Conductor connection

Tightening torque	0.4 Nm (M12 connector)
-------------------	------------------------

# SAC-3P-M12MR-M12FR SH/.../... - Sensor/actuator cable



1536078

<https://www.phoenixcontact.com/us/products/1536078>

## Connector

### Connection 1

Type	Plug angled M12
Number of positions	3
Coding type	A
Number of positions	3


### Connection 2

Type	Socket angled M12
Number of positions	3
Coding type	A
Number of positions	3

## Cable/line

Cable length	Free input (0.2 ... 40.0 m)
--------------	-----------------------------

### PUR/PVC shielded, gray [100]

Dimensional drawing	
Shielded	yes
Cable weight	38 kg/km
Cable type	PUR/PVC shielded, gray
Short symbol	LiYV1CY11Y
Cable type (abbreviation)	100
External cable diameter	5.2 mm $\pm$ 0.2 mm
Outer sheath, material	PUR
External sheath, color	gray RAL 7001
Material, inner sheath	PVC
Conductor material	Bare Cu litz wires
Conductor structure signal line	42x 0.10 mm
AWG signal line	22
Conductor cross section	0.34 mm <sup>2</sup>
Material wire insulation	PVC
Thickness, insulation	$\geq$ 0.23 mm (Core insulation)
Wire diameter incl. insulation	1.5 mm $\pm$ 0.05 mm
Single wire, color	brown, blue, black
Overall twist	3 wires, twisted


# SAC-3P-M12MR-M12FR SH/.../... - Sensor/actuator cable

1536078

<https://www.phoenixcontact.com/us/products/1536078>

Shielding	Braided copper wires
Optical shield covering	85 %
Nominal voltage, cable	≤ 300 V
Test voltage Core/Shield	≥ 2000 V
Test voltage, cable	≥ 3000 V
Cable resistance	max. 58 Ω/km (at 20 °C)
Cable insulation resistance	≥ 100 MΩ*km (at 20 °C)
Smallest bending radius, fixed installation	52 mm
Smallest bending radius, movable installation	52 mm
Number of bending cycles	2000000
Bending radius	52 mm
Traversing path	5 m
Traversing rate	3 m/s
Resistance to oil	in accordance with DIN EN 60811-2-1
Ambient temperature (operation)	-5 °C ... 80 °C (Cable, flexible installation) -25 °C ... 80 °C (cable, fixed installation)

## PVC gray [500]

Dimensional drawing	
Shielded	yes
Cable weight	40 kg/km
Cable type	PVC gray
Cable type (abbreviation)	500
External cable diameter	5.2 mm ±0.2 mm
Outer sheath, material	PVC
External sheath, color	gray RAL 7001
Conductor material	Bare Cu litz wires
Conductor structure signal line	42x 0.10 mm
AWG signal line	22
Conductor cross section	0.34 mm²
Material wire insulation	PVC
Thickness, insulation	≥ 0.23 mm (Core insulation)
Wire diameter incl. insulation	1.4 mm ±0.02 mm
Single wire, color	brown, blue, black
Overall twist	3 wires, twisted
Shielding	Tinned copper braided shield
Optical shield covering	85 %

# SAC-3P-M12MR-M12FR SH/.../... - Sensor/actuator cable



1536078

<https://www.phoenixcontact.com/us/products/1536078>

Nominal voltage, cable	≤ 300 V
Test voltage, cable	≥ 3000 V
Cable resistance	max. 58 Ω/km (at 20 °C)
Cable insulation resistance	≥ 1 GΩ*km (at 20 °C)
Resistance to oil	in accordance with DIN EN 60811-2-1
Ambient temperature (operation)	-5 °C ... 80 °C (Cable, flexible installation)
	-25 °C ... 80 °C (cable, fixed installation)

## PUR halogen-free black [PUR]

Shielded	yes
UL AWM Style	20549
Cable weight	31 kg/km
Cable type	PUR halogen-free black
Short symbol	Li9Y-VI-C-VI-11Y
Cable type (abbreviation)	PUR
External cable diameter	4.65 mm ±0.15 mm
Outer sheath, material	PUR
External sheath, color	black-gray RAL 7021
Conductor material	Bare Cu litz wires
Conductor structure signal line	42x 0.10 mm
AWG signal line	22
Conductor cross section	3x 0.34 mm <sup>2</sup> (Signal line)
Material wire insulation	PP
Thickness, insulation	≥ 0.21 mm (Core insulation)
Wire diameter incl. insulation	1.27 mm ±0.02 mm (Signal line)
Single wire, color	brown, blue, black
Overall twist	3 wires, twisted
Shielding	Braided copper wires
Optical shield covering	80 %
Nominal voltage, cable	≤ 300 V
Test voltage, cable	≥ 3000 V
Cable resistance	max. 58 Ω/km (at 20 °C)
Cable insulation resistance	≥ 100 GΩ*km (at 20 °C)
Smallest bending radius, fixed installation	23 mm
Smallest bending radius, movable installation	47 mm
Number of bending cycles	10000000
Bending radius	47 mm
Traversing path	10 m
Traversing rate	3 m/s
Acceleration	10 m/s <sup>2</sup>
Halogen-free	in accordance with DIN VDE 0472 part 815
Resistance to oil	in accordance with DIN EN 60811-2-1
Flame resistance	in accordance with UL 758/1581 FT2
	DIN EN 60332-2-2 (20 s)

# SAC-3P-M12MR-M12FR SH/.../... - Sensor/actuator cable




1536078

<https://www.phoenixcontact.com/us/products/1536078>

Other resistance	Highly resistant to acids, alkaline solutions and solvents
	hydrolysis and microbe resistant
	partly UV-resistant in accordance with DIN EN ISO 4892-2-A
Special properties	Flexible cable conduit capable
	Silicone-free
	Free of substances which would hinder coating with paint or varnish
Ambient temperature (operation)	-25 °C ... 80 °C (Cable, flexible installation)
	-40 °C ... 80 °C (cable, fixed installation)

## PVC shielded black [PVC]

Dimensional drawing	
Shielded	yes
Cable weight	40 kg/km
Cable type	PVC shielded black
Cable type (abbreviation)	PVC
External cable diameter	5.2 mm ±0.2 mm
Outer sheath, material	PVC
External sheath, color	black RAL 9005
Conductor material	Bare Cu litz wires
Conductor structure signal line	42x 0.10 mm
AWG signal line	22
Conductor cross section	3x 0.34 mm <sup>2</sup> (Signal line)
Material wire insulation	PVC
Thickness, insulation	≥ 0.23 mm (Core insulation)
Wire diameter incl. insulation	1.4 mm ±0.02 mm
Single wire, color	brown, blue, black
Overall twist	3 wires, twisted
Shielding	Tinned copper braided shield
Optical shield covering	85 %
Nominal voltage, cable	≤ 300 V
Test voltage, cable	≥ 3000 V
Cable resistance	max. 58 Ω/km (at 20 °C)
Cable insulation resistance	≥ 100 MΩ*km (at 20 °C)
Resistance to oil	in accordance with DIN EN 60811-2-1
Flame resistance	As per UL-Style 2464
Ambient temperature (operation)	-5 °C ... 80 °C (Cable, flexible installation)

# SAC-3P-M12MR-M12FR SH/.../... - Sensor/actuator cable



1536078

<https://www.phoenixcontact.com/us/products/1536078>

	-25 °C ... 80 °C (cable, fixed installation)
--	--

## Environmental and real-life conditions

### Ambient conditions

Degree of protection	IP65
	IP67
Ambient temperature (operation)	-25 °C ... 90 °C (Plug / socket)

## Standards and regulations

Standard designation	M12 connector
Standards/specifications	IEC 61076-2-101

# SAC-3P-M12MR-M12FR SH/.../... - Sensor/actuator cable



1536078

<https://www.phoenixcontact.com/us/products/1536078>

## Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/1536078>



### EAC

Approval ID: RU C-DE.BL08.B.00286



### UL Listed

Approval ID: FILE E 221474

	Nominal voltage $U_N$	Nominal current $I_N$	Cross section AWG	Cross section $\text{mm}^2$
	300 V	4 A	-	-



### cUL Listed

Approval ID: FILE E 221474

	Nominal voltage $U_N$	Nominal current $I_N$	Cross section AWG	Cross section $\text{mm}^2$
	300 V	4 A	-	-



### EAC-RoHS

Approval ID: RU D-DE.HB35.B.00387

### cULus Listed



# SAC-3P-M12MR-M12FR SH/.../... - Sensor/actuator cable



1536078

<https://www.phoenixcontact.com/us/products/1536078>

## Classifications

### ECLASS

ECLASS-11.0	27060311
ECLASS-12.0	27060311
ECLASS-13.0	27060311

### ETIM

ETIM 8.0	EC001855
----------	----------

### UNSPSC

UNSPSC 21.0	26121600
-------------	----------

# SAC-3P-M12MR-M12FR SH/.../... - Sensor/actuator cable



1536078  
<https://www.phoenixcontact.com/us/products/1536078>

## Environmental product compliance

REACH SVHC	Lead 7439-92-1
China RoHS	Environmentally Friendly Use Period = 50 years
	For information on hazardous substances, refer to the manufacturer's declaration available under "Downloads"

Phoenix Contact 2023 © - all rights reserved  
<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)